



People's Democratic Republic of Algeria
Ministry of Higher Education and Scientific Research
University M'hamed Bougara of Boumerdes
Faculty of Technology



Laboratory of Energetic, Mechanics and Engineering



2nd National Conference on Green Energy (NCGE'24)

December 15th & 16th, 2024, Boumerdes, Algeria

<http://ncge.univ-boumerdes.dz>

Book of Abstracts

Editors

Nabil HIMRANE Yassine

YAKHELEF Mohamed

KAOUANE Meziane

HAMEL

Nour El-Houda GABOUR

Said ALEM

Ratiba FELLAG

Madjid HACHEMI

Nidhal CHERRAT

Copyright © NCGE2024

All Rights Reserved by the 2nd National Conference on Green Energy.

ISBN: 978-9969-9879-0-4

Dépôt légal:-2024



2nd National Conference on Green Energy
NCGE'24
15th & 16th December 2024
Boumerdes - Algeria



COMMITTEES

Honorary Chairs

Pr. YAHY Mustepha, Rector of the University
Pr. SAIDI Mohamed, Dean of the Faculty of Technology

Conference General Chairs

Dr. HIMRANE Nabil, University of Boumerdes
Dr. KAOUANE Mohamed, University of Boumerdes

Organizing Committee Chair

Dr. YAKHELEF Yassine, University of Boumerdes

Scientific Committee Chair

Dr. HAMEL Meziane, University of Boumerdes

Organizing Committee

Dr. ALEM Said, University of Boumerdes
Dr. CHERRAT Nidhal, University of Boumerdes
Dr. FELLAG Ratiba, CDTA
Dr. HALOUANE Yacine, University of Boumerdes
Dr. GABOUR Nour El Houda, University of Boumerdes
Dr. MOUALEK Riad, University of Tizi-Ouzou
Dr. MOUATSI Abdelmalek – University of Constantine
Dr. MOUGARI Nour El-Islam, University of Boumerdes
Dr. OUALI Sofiane, University of Boumerdes
Dr. OUCHIKH Sara, University of Boumerdes





2nd National Conference on Green Energy
NCGE'24
15th & 16th December 2024
Boumerdes - Algeria



Scientific Committee

- Dr. ABERKANE Sofiane – University of Bouira
Dr. ABDESLAME Djamila – University of Boumerdes
Dr. AIT-CHIKH Mohamed – University of Boumerdes
Pr. AKNOUCHE Hamid – University of Boumerdes
Dr. ALALA Nabil – USTHB Algiers
Pr. AMEZIANI Djamel Eddine – USTHB Algiers
Dr. AMROUCHE Bessam – University of Bejaia
Dr. AOUZELLAG Haroun – University of Béjaïa
Dr. BELKACEM Samia – University of Boumerdes
Dr. BENAMMAR Samir – University of Boumerdes
Dr. BENBELLIL Abdelali – University of Boumerdes
Dr. BENSIDHOUM Tarek – University of BBA
Pr. BENTARZI Hamid – University of Boumerdes
Dr. BERRAZOUANE Sofiane – University of Boumerdes
Dr. BOUAMRENE Mohamed – University of Boumerdes
Pr. BOUHERAOUA Mustapha – University of Tizi-Ouzou
Pr. BOUKHELIFA Akkila – USTHB Algiers
Dr. BOUNAR Amina – USTHB Algiers
Pr. BOUZIDA Ahcene – University of Bouira
Dr. BRAHIMI Faiza – University of Boumerdes
Pr. CHELLIL Ahmed – University of Boumerdes
Dr. DAIMALLAH Ahmed – University of Boumerdes
Pr. DENOUN Hakim – University of Tizi-Ouzou
Dr. DERMOUCHE Reda – ENSTA Algiers
Dr. DICHOU Karima – University of Boumerdes
Dr. DOMANE Radia – University of Boumerdes
Pr. GHEDAMSI Kaci – University of Bejaia
Pr. GRINE Ali – University of Boumerdes
Dr. GUEMADI Samah – University of Boumerdes
Dr. GUERRACHE Fadila – University of Boumerdes
Pr. HACHEMI Madjid – University of Boumerdes
Dr. HADDAD Mohammed – CRTI Algiers
Dr. HAROUN Radia – University of Boumerdes
Dr. HIMRI Youcef – University of Bechar
Dr. HOUASSINE Hamza – University of Bouira
Pr. KADRI Mohamed – University of Boumerdes
Dr. LAMRI Younes – University of Boumerdes
Pr. LECHEB Samir – University of Boumerdes
Dr. Lakhlef Ahcene – University of Tizi-Ouzou
Dr. LEKOUAGHET Badis – CRTI Algiers
Pr. LOUNICI Mohand Said – University of Boumerdes
Dr. Madaci Bouthaina – University of Boumerdes
Dr. MANSER Younes Belkacem – University of Boumerdes
Pr. MANSOURI Kacem – University of Boumerdes
Dr. MECHAKRA Hamza – University of Boumerdes
Dr. MEDELFEF Abdessamed – USTHB Algiers
Dr. MESSAID Bachir Eddine – University of Boumerdes
Pr. MESSAOUDI Noureddine – University of Boumerdes
Dr. MILOUDI Lalia – University of Boumerdes
Pr. MZIOU Nassima – University of Boumerdes
Dr. NAFAA Fares – University of Jijel
Dr. NAÏT-OUSLIMANE Ahmed – University of Tizi-Ouzou
Dr. OUADFEL Ghania – USTHB Algiers
Dr. RAGUEB Haroun – University of Boumerdes
Dr. Ratni Azeddine – University of Boumerdes
Dr. RIACHE Samah – University of Boumerdes
Pr. SAFI Brahim – University of Boumerdes
Dr. SOUKHAL Abdelkarim – University of Boumerdes
Dr. Tsebia Mohamed – University of Boumerdes
Dr. TOUBAL MAAMAR Alla Eddine – University of Boumerdes
Dr. ZARGA Djaloul – University of Boumerdes
Dr. ZARITA Rahouadja – University of Boumerdes
Pr. ZAOUIA Mustapha – University of Tizi-Ouzou





2nd National Conference on Green Energy
NCGE'24
15th & 16th December 2024
Boumerdes - Algeria



ABOUT NCGE'24

The second National Conference on Green Energy (NCGE'24) is a peer-reviewed conference on Renewable and Sustainable Energy held at the University of Boumerdes during December 15-16, 2024. The conference serves as an exclusive forum for researchers, academics and industry professionals to present and discuss the latest technological advancement as well as future directions and trends in the field of Renewable and Sustainable Energy.

The conference includes several keynote lectures, academic discussions, oral and poster presentations, technical workshops and a social event that will provide huge networking opportunities for all the attendees.

Thank you for joining us at NCGE'24 to be a part of this important event shaping the future of Renewable and Sustainable Energy.





Contents

Prototype Implementation of a Distributed Renewable Energy Micro-Power Plants	9
An Improved Parameter Identification of PEM Fuel Cells Using Puma Optimization Algorithm	10
Improvement of Paraffin Melting Process Using Additional Metals Algorithm	11
Ab-initio Study of Optoelectronic and Elastic Properties of Halide Double Perovskite Cs ₂ BiAgBr ₆	12
Modeling in MATLAB/SIMULINK of a Wind Turbine Connected to a Doubly-Fed Induction Generator	13
Etude et Conception d'un Banc D'essais pour un Émulateur Éolien de Petite Puissance	14
Impact of Cooling Rate on Structure and Hardness of 30crmnti Steel before and after Carburizing Treatment	15
Synthesis of Supported Metal Oxide Catalysts for Natural Gas Conversion	16
Control of BLDC Motor Speed for Pumping Systems Using Fuzzy Logic-PI	17
Design of Fuzzy-Sliding Mode and Comparison with Different Modes for MPPT Connected to a Load	18
Analyse CFD de L'écoulement du Peroxide D'hydrogène dans un Lit Catalytique d'un Propulseur à Monergol de 20N	19
Enhancing PV System Grid Integration through a Dual-Stage Configuration and Model Predictive Control of a PUC5 Inverter	20
Advancements and Applications of Energy Harvesting Technologies in Wearable Devices: Feasibility, Integration, and Future Directions	21
Shading Effect on Mono-Crystalline PV Module Performance Installed in Annaba, Algeria	22
Effect of Rectangular Fin Arrangement on the Melting Process of Nanoparticle-Enhanced Phase Change Materials	23
Design and Experimental Analysis of a Linear Fresnel Collector for Solar Desalination in Algeria	24





2nd National Conference on Green Energy
NCGE'24
15th & 16th December 2024
Boumerdes - Algeria



DFIG-WECS Speed-Sensorless IGBT Open Circuit Fault Optimization Using Fuzzy Sliding Mode Observer	25
Improving the Performance of a Hybrid Solar Panel PV/T Using a Solid Corrugated Strip Insert and Water/MWCNT Nanofluid in the Coolant Tubes	26
Analysis of Low-Frequency Oscillation in Power System with Renewable Energy Sources	27
Physical Properties of New Ternary Chalcogenide Copper Molybdate Sulfur I- Cu_2MoS_4	28
Cold Production Using Solar Energy	29
Computational Evaluation of Curved Tube Receiver Performance: Comparing Thermo-Hydraulic Impacts of Nanofluids and Conventional Fluids	30
Improved Super-Twisting Sliding Mode Control of twostage PV Grid-Connected Converter	31
Simulation d'un Système PV/Pile à Combustible avec Stockage pour une Ferme Laitière	32
Thermogravimetric and Kinetic Analysis of Syagrus Romanzoffiana Fibers for Alternative Renewable Energy Systems	33
Effectiveness in the Safety and Security of Energy Systems Case of Risk Management in Electricity Power Plant	34
A Genetic Algorithm for an Optimum Design in Composite Laminate	35
Influence of the Convergent-Divergent Form of the Collector on the Flow Behavior inside A SCPP	36
Lumped Parameter Thermal Network Model of Three Phase Induction Motor	37
Finite Element Analysis of a Tubular Linear Generator for Wave Energy Conversion	38
High Efficiency Photocatalytic Hydrogen Production over Ternary System PANI- MnO_2 - Agbr: Physical, Electrochemical and Optical Properties Studies	39
Integration of Biomass Energy into the Essential Oil Extraction Process	40
Fractal Dimension as a Diagnostic Tool for Signal Analysis in Polluted High-Voltage Insulators	41
Enhanced Secondary Control Design for Three Phase VSI-based Microgrids	42





2nd National Conference on Green Energy
NCGE'24
15th & 16th December 2024
Boumerdes - Algeria



Experimental Implementation of Fuzzy Logic Based Energy Management for Horizon PEM Fuel Cell/Ultra Capacitor System	43
Passivity-Based Control Approach for Electric Vehicle Optimization	44
Thermal Performance of Wavy Channel Heat Exchange	45
Assessing the Role of Solar Irradiance Parameters in WRF Simulations: Implications for Climate Modeling and Renewable Energy Applications	46
Evaluating Power Control Techniques for DFIGWT: A Comparison of Direct, Fuzzy Direct, and Indirect Control Methods	47
Enhancing Electric Power Quality of AWPS by Modified Bridgeless SEPIC PFC Converter	48
Performance Enhancement of DC-DC Boost Converter Using PSO-Optimized PI Controller	49
Application of Artificial Neural Networks for the Modeling of a Dual Fuel Diesel Engine Powered by Different Hydrogene Fractions	50
Prediction and Optimization of Performance Parameters and Emissions Characteristics of a Diesel Engine Fueled by Castor Oil-Based Biodiesel	51
Simulation de la Dégradation de Performance Électrique d'un Module Photovoltaïque avec Fissuration	52
Numerical Study of Thermal Efficiency Ventilated Cavity Using the LBM-MRT	53
Enhancing the Quality of Electrical Energy Generation in Wind Energy Conversion Systems Using Robust Sliding Mode Control	54
Design and Implementation of a DC-DC boost converter for a Photovoltaic Water Pumping System	55
Modeling Biohydrogen Production from Organic Wastes via Dark Fermentation using Artificial Neural Networks	56
Effet de la Richesse sur des Flammes de Méthane Hydrogène	57
Simulation Numérique de la Combustion du CH_4 Enrichi au H_2	58
Improving Power Quality and Dynamic Performance of Modular Multilevel Converter based Microgrid Solar System using Intelligent MPPT controller	59





2nd National Conference on Green Energy
NCGE'24
15th & 16th December 2024
Boumerdes - Algeria



Prediction of Engine Performance for an Hydrogen Dual Fueled Diesel Engine using Artificial Neural Network	60
Optimization of Heat Exchanges in Forced Convection at the Level of a Fin Exchanger	61
Advanced Photovoltaic Pumping System Modelling and MPPT Control via Bond Graph	62





2nd National Conference on Green Energy
NCGE'24
15th & 16th December 2024
Boumerdes - Algeria



Paper ID : 4

Prototype Implementation of a Distributed Renewable Energy Micro-Power Plants

Z. Dekali
LAT, Laboratoire d'Automatique de Tlemcen
Université de Tlemcen 13000, Tlemcen, Algeria

Abstract

In an increasingly pressing ecological context, this paper makes a contribution to the field of renewable energy. The main objective of this project is to manage the production of electricity from renewable energies (wind and photovoltaic) without creating disturbances in the network, and to absorb them if they occur through load variation over time. We are developing strategies to control micropower plants so that each one produces an exact amount of energy in real time to keep pace with variations in consumption and overcome the limitations of weather variations.

Keywords

Renewable energy - Micro power plant - Wind energy - Solar energy - Wind turbine emulator





2nd National Conference on Green Energy
NCGE'24
15th & 16th December 2024
Boumerdes - Algeria



Paper ID : 8

An Improved Parameter Identification of PEM Fuel Cells Using Puma Optimization Algorithm

Aissa Rebai
Département d'Automatique et
d'Électromécanique Faculté des Sciences et
de la Technologie
Université de Ghardaia, Algeria

El Mouatez Billah Messini
Department of Electrical Engineering,
Faculty of Applied Sciences, Laboratoire
LAGE
University of Ouargla, Algeria, Sonatrach -
Institut Algérien du Pétrole - École de
Hassi Messaoud

Abstract

The focus of this paper is on the parameter identification of Proton Exchange Membrane (PEM) fuel cells. To determine the optimal parameters for the system, a puma optimization algorithm (POA) is employed which uses a fitness function based on the Integral of the Squared Error (ISE). Experiments are carried out to prove the correctness of the proposed approach. This paper also provides a comparison of results with existing approaches available in the literature and argues that the methods reported here are much more effective in estimating the parameters of a PEM fuel cell.

Keywords

PEM fuel cell - modelling - identification - metaheuristic algorithms - optimization.





2nd National Conference on Green Energy
NCGE'24
15th & 16th December 2024
Boumerdes - Algeria



Paper ID : 9

Improvement of Paraffin Melting Process Using Additional Metals Algorithm

Khaoula Missoum
ETAP Laboratory, Department of
Mechanics
University of Tlemcen FT BP 230, 13000
Tlemcen, Algeria

Abdel Illah Nabil Korti
ETAP Laboratory, Department of
Mechanics
University of Tlemcen FT BP 230, 13000
Tlemcen, Algeria

Hocine Guellil
ETAP Laboratory, Department of
Mechanics
University of Tlemcen FT BP 230, 13000
Tlemcen, Algeria

Abstract

Phase change thermal storage is an innovative and promising technology for saving energy. It is one of the new areas of research because it provides the solution to problems related between the provided and the required energies. Paraffin is a common phase change material (PCM) that used in many applications in thermal energy storage (TES) systems. However, the main disadvantage is their low thermal conductivities. However, using metallic additives to improve effective thermal conductivity of PCM can lead to decreasing effective heat capacity and the thermal energy stored. An experimental study was carried out to analyze the thermal behavior of the paraffin melting in a thermal cavity integrating different metals (zamak, aluminum and copper) with different configuration. The originality of study is to try to predict the best duo that respects both the improvement of thermal conductivity and energy stored. The experiments show that adding aluminum perforated plate in paraffin accelerates the melting process by about 19% and increases the energy stored by 5.18%.

Keywords

Experimental study - PCM - effective thermal - conductivity - energy stored.





2nd National Conference on Green Energy
NCGE'24
15th & 16th December 2024
Boumerdes - Algeria



Paper ID : 11

Ab-initio Study of Optoelectronic and Elastic Properties of Halide Double Perovskite Cs₂BiAgBr₆

Tahar Bellakhdar
Computational Materials Physics
Laboratory (CMPL), Materials and
Sustainable Development Department,
Faculty of Exact Sciences
Djillali Liabes University of Sidi Bel Abbès,
22000 Sidi Bel Abbès, Algeria

Hamza Sacia Zakia Nabi
Computational Materials Physics
Laboratory (CMPL), Materials and
Sustainable Development Department,
Faculty of Exact Sciences
Djillali Liabes University of Sidi Bel Abbès,
22000 Sidi Bel Abbès, Algeria

Badra Bouabdallah
Computational Materials Physics
Laboratory (CMPL), Materials and
Sustainable Development Department,
Faculty of Exact Sciences
Djillali Liabes University of Sidi Bel Abbès,
22000 Sidi Bel Abbès, Algeria

Abstract

The present study reports on the electronic, optical and elastic properties of Cs₂AgBiBr₆ halide double perovskite using the full potential linearized augmented plane wave method (FP-LAPW). The generalized gradient approximation (GGA) and the TranBlaha modified Becke-Johnson exchange potential (mBJ) were applied to improve the band structure and optical properties for this material. Good agreement with experiment for lattice parameters demonstrates the high precision of our approach, also the elastic and mechanical properties indicate that Cs₂AgBiBr₆ have a ductile and anisotropic nature. The band structure calculations reveal semiconductor character with an indirect band gap (2.02 eV) and maximum absorption in the visible spectrum (104 – 105 cm⁻¹) very appreciated for photovoltaic and optoelectronic.

Keywords

Halide Double Perovskite - FP-LAPW - GGA - mBJ.





2nd National Conference on Green Energy
NCGE'24
15th & 16th December 2024
Boumerdes - Algeria



Paper ID : 13

Modeling in MATLAB/SIMULINK of a Wind Turbine Connected to a Doubly-Fed Induction Generator

Brahim Dahhou
LDEE-laboratory, Dept. of Electrical
Engineering
University of Science and Technology
Mohamed Boudiaf, El Mnaouar, BP 1505,
Bir El Djir 31000, Oran Oran, Algeria

Ahmed Bouraiou
Unité de Recherche en Energie
Renouvelables en Milieu Saharien
URERMS Centre de Développement des
Energies Renouvelables, CDER, 01000
Adrar Adrar, Algeria

Abstract

This work concerns, the modeling of a wind turbine system using a wind turbine with a horizontal axis a variable speed connected to a Doubly-Fed Induction Generator (DFIG). We designed a control that allowed us to maximize the received power. This models was developed in Matlab /Simulink to analyze the performance of the wind system.

Keywords

Wind turbine - DFIG - modeling - active and reactive power.





2nd National Conference on Green Energy
NCGE'24
15th & 16th December 2024
Boumerdes - Algeria



Paper ID : 14

Etude et Conception d'un Banc D'essais pour un Émulateur Éolien de Petite Puissance

Tahar Bellakhdar
Centre de Développement des Energies
Renouvelables, CDER, BP 62 Route de
l'Observatoire, Bouzaréah, Alger, 16340,
Algérie

Hamza Sacia Zakia Nabi
Centre de Développement des Energies
Renouvelables, CDER, BP 62 Route de
l'Observatoire, Bouzaréah, Alger, 16340,
Algérie

Badra Bouabdallah
Centre de Développement des Energies
Renouvelables, CDER, BP 62 Route de
l'Observatoire, Bouzaréah, Alger, 16340,
Algérie

Résumé

Dans ce travail, les auteurs présentent un émulateur éolien à petite échelle basé sur un moteur asynchrone et un variateur de vitesse. Les performances aérodynamiques et la méthode de calcul du coefficient de puissance de la turbine éolienne sont déterminées avec le programme PropID. Le mode opératoire du banc d'essai est expliqué à l'aide des équations et des schémas synoptiques. Les résultats théoriques sont comparés à ceux issus des relevés expérimentaux.

Mots-clés

Emulateur éolien - Variateur de vitesse - Simulateur HIL - Energies renouvelables.





2nd National Conference on Green Energy
NCGE'24
15th & 16th December 2024
Boumerdes - Algeria



Paper ID : 15

Impact of Cooling Rate on Structure and Hardness of 30CrMnTi Steel before and after Carburizing Treatment

Saoudi Abdenour
Laboratory of Engineering and
Sciences of Advanced Materials
(ISMA) Abbas Laghrour University
Khenchela , Algeria

Mebrouki Toufik
Laboratory of Engineering and
Sciences of Advanced Materials
(ISMA) Abbas Laghrour University
Khenchela , Algeria

Aissani Linda
Mater Science Department
Abbas Laghrour University
Khenchela , Algeria

Bouamrane Mouhamed Saïd
Unité de Recherche Matériaux
Procédés and Environnement
Université M'Hamed Bougara,
Boumerdes, Algérie

Abstract

The aim of our work is to examine the effect of cooling rate on the structure and hardness of 30CrMnTi steel before and after carburizing, using Jominy specimens. Three types of specimen were analyzed: E1 (untreated), E2 (austenitized and end-hardened) and E3 (case-hardened then end-hardened). Metallographic analyses show that the untreated steel exhibits globular pearlite with a uniform hardness of 195 HV in all zones. For specimen E2, maximum hardness (567 HV) is observed at 1.5 mm from the bottom surface, with a martensite and bainite structure, while it decreases to 258 HV at 95 mm, where the structure consists of ferrite and pearlite. By contrast, specimen E3 (carburized and end-hardened) gives a maximum hardness of 868 HV at 1.5 mm, due to the formation of martensite + bainite+Fe₃C, where it progressively decreases with greater Jominy distance. Finally, the cooling rate has a major impact on the structure and hardness of 30CrMnTi steel.

Keywords

30CrMnTi - Jominy test - carburization - structure - hardness.





2nd National Conference on Green Energy
NCGE'24
15th & 16th December 2024
Boumerdes - Algeria



Paper ID : 17

Synthesis of Supported Metal Oxide Catalysts for Natural Gas Conversion

Yousra Abdelbaki
Hydrogen Energy Applications Laboratory,
Faculty of Technology
University of Blida 1, Algeria

Rachid Issaadi
Hydrogen Energy Applications Laboratory,
Faculty of Technology
University of Blida 1, Algeria

Abstract

This study is set within the framework of the ongoing energy transition, which involves the gradual substitution of non-renewable fossil fuels with renewable feedstocks for the production of chemicals and fuels. During this transitional phase, fossil sources, particularly natural gas, play a pivotal role, as highlighted by recent energy outlooks. A study on the use of metal oxide catalysts for various reactions has been conducted, with a focus on the oxidative dehydrogenation of ethane (ODHE) using NiO/alumina catalysts. The relationship between the catalytic performance of these catalysts and their preparation methods has been investigated. To optimize catalytic performance, selective supported NiO catalysts for ODHE to ethylene were synthesized by fine-tuning synthesis parameters. The catalysts were characterized using a range of physicochemical techniques, including X-ray diffraction (XRD), nitrogen adsorption (N_2 -adsorption) temperature-programmed reduction (TPR) and X-ray photoelectron spectroscopy (XPS). It was found that both the preparation method significantly affects the catalytic performance of nickel oxide. Catalysts with strong Ni-support interaction and low reducibility exhibited the highest selectivity towards ethylene, while those with weaker interactions were less selective for the olefin. The mechano-chemical synthesis of NiO/alumina catalysts or the addition of oxalic acid during preparation was shown to negatively impact olefin formation. The influence of structural and surface properties on ethane ODHE, particularly on ethylene selectivity, is also discussed in detail.

Keywords

ODH of ethane - nickel - NiO-support interaction - ethylene.





2nd National Conference on Green Energy
NCGE'24
15th & 16th December 2024
Boumerdes - Algeria



Paper ID : 19

Control of BLDC Motor Speed for Pumping Systems Using Fuzzy Logic-PI

Meryem Lagoune
Electrical Engineering
Département
Automatic Laboratory of
Setif-LAS, Setif, Algeria

Samia Latreche
Electrical Engineering
Département
Automatic Laboratory of
Setif-LAS, Setif, Algeria

Mabrouk Khemliche
Electrical Engineering
Département
Automatic Laboratory of
Setif-LAS, Setif, Algeria

Badreddine Babes
Reaserch Center In
Industrial Technologies
CRTI, P.O.box
64,Cheraga 16014,
Algiers, Algeria

Hamza Khemliche
Reaserch Center In
Industrial Technologies
CRTI, P.O.box
64,Cheraga 16014,
Algiers, Algeria

Abstract

The use of Brushless Direct Current Motors (BLDC) in industrial applications is increasing due to their high efficiency and reliability. However, controlling the speed of these motors, particularly in pumping applications, presents challenges due to their nonlinear nature and parameter uncertainties. To achieve superior speed control in such scenarios, the use of a fuzzy logic controller (FLC), known for its ability to effectively handle uncertainties and nonlinear systems. This research aims to design and analyze the performance of FLC for controlling the speed of a BLDC motor used in a pumping application using Matlab/Simulink. The performance of the FLC is compared with traditional control techniques in terms of time response and stability.

Keywords

BLDC motor - Pumping system - fuzzy logic-based - PI-controller - Matlab/Simulink.





2nd National Conference on Green Energy
NCGE'24
15th & 16th December 2024
Boumerdes - Algeria



Paper ID : 21

Design of Fuzzy-Sliding Mode and Comparison with Different Modes for MPPT Connected to a Load

Bouguerra Khoukha
Automatic Laboratory of Setif,
Electrical Engineering Department
University of Setif1, Setif, Algeria

Samia Latreche
Automatic Laboratory of Setif,
Electrical Engineering Department
University of Setif1, Setif, Algeria

Mabrouk Khemliche
Automatic Laboratory of Setif,
Electrical Engineering Department
University of Setif1, Setif, Algeria

Hamza Khemliche
Reaserch Center In Industrial
Technologies CRTI
P.O.box 64,Cheraga 16014 Algiers,
Algeria

Abstract

This research discusses the importance of comparing maximum power point tracking (MPPT) technologies in renewable energy systems, especially in photovoltaic (PV) systems. The goal is to study and compare four MPPT technologies: perturb and Observe (*P&O*), Fuzzy Logic Control (FLC), slip mode control (SMC), and fuzzy sliding mode control (FSMC). The photoelectric model and DC-DC power adapter are designed in the MATLAB/Simulink simpler Systems toolbox and the MPPT algorithms are tested under different operating conditions to analyze the performance and limitations of each algorithm. The results are presented through graphs, highlighting the strengths, weaknesses of each technique; the results and discussion include a comparison of the performance of the techniques, focusing on efficiency, convergence time, stability, and durability. The paper concludes with a summary and recommendations for choosing the most suitable MPPT technique.

Keywords

Photovoltaic (PV) - Maximum power point tracking (MPPT) - Fuzzy logic control (FLC) - Sliding mode control (SMC) - Fuzzy-sliding mode control (FSMC).





2nd National Conference on Green Energy
NCGE'24
15th & 16th December 2024
Boumerdes - Algeria



Paper ID : 24

Analyse CFD de L'écoulement du Peroxide D'hydrogène dans un Lit Catalytique d'un Propulseur à Monergol de 20N

Fadéla Benzenine
Département de Génie Mécanique
Laboratoire de Thermique
Energétique et Appliquée ETAP
Faculté de Technologie, Tlemcen,
Algérie

Chakib Seladji
Département de Génie Mécanique
Laboratoire de Thermique
Energétique et Appliquée ETAP
Faculté de Technologie, Tlemcen,
Algérie

Djamal Darfilal
Centre de développement des
satellites
L'Agence Spatiale Algérienne
Oran, Algérie

Othman Bendermel
Centre universitaire de Maghnia,
Tlemcen, Algérie

Résumé

Cette étude, une analyse bidimensionnelle, a été réalisée à l'aide du logiciel de dynamique des fluides numérique (CFD) ANSYS Fluent afin de simuler l'écoulement du fluide à travers dans le lit catalytique du propulseur à monergol system pour les applications spatiales. Le fluide utilisé est le peroxyde d'hydrogène (H₂O₂) comme propergol vert, à une concentration de 87,5% avec un lit catalytique constitué de particules d'argent sphériques identiques. La méthode des volumes finis a été utilisée pour résoudre l'équation gouvernante. Une approche mathématique basée sur le modèle de non-équilibre thermique local (LTNE) a été utilisée pour décrire le transfert de chaleur à travers les phases solides et fluides. La simulation a permis d'optimiser les performances du lit catalytique pour une décomposition optimale du peroxyde d'hydrogène et de générer la poussée requise de 20N.

Mots-clés

Peroxyde d'hydrogène - Propergol vert - Lit catalytique - Propulseur à monergol.





2nd National Conference on Green Energy
NCGE'24
15th & 16th December 2024
Boumerdes - Algeria



Paper ID : 26

Enhancing PV System Grid Integration through a Dual-Stage Configuration and Model Predictive Control of a PUC5 Inverter

Soufian Khettab
SET Laboratory,
Faculty of
Technology,
Electronics
Department Blida 1
University, 09000
Blida, Algeria

Intissar Hattabi
SET Laboratory,
Faculty of
Technology,
Electronics
Department Blida 1
University, 09000
Blida, Algeria

Aissa Kheldoun
Laboratory of Signals
& Systems, Institute
of Electrical and
Electronic
Engineering
University M'hamed
Bougara, Boumerdes
35000, Algeria

Oussama Merabet
Laboratory of Signals
& Systems, Institute
of Electrical and
Electronic
Engineering M'hamed
Bougara, Boumerdes
35000, Algeria

Rafik Bradai
LATSI, Faculty of
Technology,
Electronics
Department
Blida 1 University,
09000 Blida, Algeria

Hamza Belmadani
SET Laboratory,
Faculty of
Technology,
Electronics
Department Blida 1
University, 09000
Blida, Algeria

Abstract

This paper presents a dual-stage, single-phase photovoltaic (PV) system connected to the grid through a fivelevel Packed U-Cell (PUC5) inverter, controlled by Model Predictive Control (MPC). The system is designed to optimize grid integration by delivering superior current injection with minimal Total Harmonic Distortion (THD), ensuring reactive power compensation, and maximizing the efficient extraction and injection of power from the PV source. The simulation findings validate the resilience and viability of the system by demonstrating how well the suggested control strategy improves power quality, responsiveness, and accuracy under a range of weather situations.

Keywords

multilevel inverter - PUC5 - dual-stage - MPC controller - MPPT - THD.





2nd National Conference on Green Energy
NCGE'24
15th & 16th December 2024
Boumerdes - Algeria



Paper ID : 27

Advancements and Applications of Energy Harvesting Technologies in Wearable Devices: Feasibility, Integration, and Future Directions

Benterki Touba
Institute of architecture and urbanisme
LEVE Lab
University of Batna 1, Batna, Algeria

Guettafi Manel
Institute of architecture and urbanisme
LEVE Lab
University of Batna 1, Batna, Algeria

Abstract

The fast spread of wearable technology, spanning gadgets such as smartwatches and fitness trackers, has substantially altered personal health management and everyday convenience. Despite these developments, the need on external power sources—particularly batteries—poses considerable obstacles, including bulkiness, frequent recharging, and general discomfort. To alleviate these challenges, energy harvesting technologies provide a possible alternative by turning ambient energy into electrical power, therefore allowing wearables to function independently. This research critically assesses the feasibility and promise of merging three main energy harvesting technologies—piezoelectric, the rmoelectric, and photovoltaic—into wearable devices. Through an in-depth investigation of performance parameters such as power production, efficiency, durability, and environmental impact, the research reveals the most effective techniques for utilizing these technologies. The findings demonstrate that each energy harvesting technique provides distinct strengths and limits, but their combined usage may greatly boost device functioning and sustainability. The research suggests that adding energy harvesting into wearable technology not only increases user comfort and operational autonomy but also promotes the possible uses and environmental advantages of future wearable devices. functionality of wearable gadgets. By solving these hurdles, energy harvesting has the potential to alter the area of wearable technology, allowing creative applications and extending the possibilities for autonomous, self-powered devices.

Keywords

Energy Harvesting - Wearable Technology - Piezoelectric Devices - Thermoelectric Generators - Photovoltaic Cells.





2nd National Conference on Green Energy
NCGE'24
15th & 16th December 2024
Boumerdes - Algeria



Paper ID : 28

Shading Effect on Mono-Crystalline PV Module Performance Installed in Annaba, Algeria

Billel Lamri
dept. Electrical Engineering
Badji mokhtar university Annaba,
Algeria

Ali Ouanas
dept. Electrical Engineering
University 20 août 1955 Annaba,
Algeria

Ramzi Benaicha
dept. Electronic Engineering
Engineering Badji mokhtar
university Annaba, Algeria

Akram Messikh
dept. electromechanical
Badji mokhtar university Annaba,
Algeria

Abstract

This article presents an experimental study on the photovoltaic module installed in Annaba. We have described the importance of bypass diodes on the performance and efficiency of photovoltaic system, and their roles of protecting photovoltaic modules from hot spots causing the deterioration and destruction of PV module. A PV module model was proposed on the MATLAB/ Simulink environment, which precisely describes the Current-Voltage and PowerVoltage characteristics, of PV module under the climate of Annaba and the impact of partial shade. The obtained results were compared with practical databases, confirming the stability and performance of the proposed model.

Keywords

Mono-crystalline PV module - partial shading - Matlab/Simulink model - PV module characteristic.





Paper ID : 29

Effect of Rectangular Fin Arrangement on the Melting Process of Nanoparticle-Enhanced Phase Change Materials

Saddam Hocine Mellah
Laboratoire de Physique
Quantique de la Matière
et Modélisation
Mathématique
University of Mustapha
Stambouli of Mascara
Mascara, Algeria

Samir Laouedj
Laboratory of
Materials and
Reactive Systems,
LMSR
Djillali Liabes
University of Sidi Bel
Abbes Sidi Bel
Abbes, Algeria

Ali Bouziane
Laboratory of
Materials and
Reactive Systems,
LMSR
Djillali Liabes
University of Sidi Bel
Abbes Sidi Bel
Abbes, Algeria

Ilias Benyahia
Laboratoire de
Physique Quantique
de la Matière et
Modélisation
Mathématique
University of
Mustapha Stambouli
of Mascara Mascara,
Algeria

Manal Lakhdari
Laboratoire de
Physique Quantique
de la Matière et
Modélisation
Mathématique
University of
Mustapha Stambouli
of Mascara Mascara,
Algeria

Abderrahmane Aissa
Laboratoire de
Physique Quantique
de la Matière et
Modélisation
Mathématique
University of
Mustapha Stambouli
of Mascara Mascara,
Algeria

Abstract

Phase change materials (PCMs) are essential components of thermal energy storage systems, with their thermal storage rate linked to the melting rate and heat distribution. The problem of slow heat transfer, particularly in the lower layers of PCM capsules, has been identified as a significant challenge. This research aims to improve the heat distribution and melting rate of nanoparticle-enhanced PCMs (NEPCMs) in octagonal-shaped shell capsules by incorporating dendrite-shaped fins. The research contribution is the investigation of three distinct fin configurations: random arrangement (case 1), downward decrease in fin length (case 2), and downward increase in fin length (case 3), along with varying nanoparticle volume fractions ($\phi = 0\%$, 3% , and 6%). The method used for simulating heat transfer during phase change is the porosity enthalpy method. The results indicate that integrating fins and increasing the nanoparticle concentration enhances the thermal conductivity of the PCM. Case 3, which involves downward increasing fin length, demonstrated the highest heat transfer rate and the shortest fusion time, reducing the melting rate by 15% compared to case 2. Furthermore, the study reveals that a nanoparticle concentration of $\phi = 6\%$ results in a 20% decrease in melting rate and the smallest decline in the average Bejan number. In conclusion, the use of dendritic fins and nanoparticle-enhanced PCMs significantly improves thermal performance, especially in the outer layers of the PCM capsules.

Keywords

NEPCM - Melting process - FEM - Heat transfer - Fin - Latent Heat Thermal Energy Storage.





2nd National Conference on Green Energy
NCGE'24
15th & 16th December 2024
Boumerdes - Algeria



Paper ID : 33

Design and Experimental Analysis of a Linear Fresnel Collector for Solar Desalination in Algeria

Kacimi Yasmine
Laboratory of Physical Chemistry
of Material Interfaces Applied to
the Environment Department of
Renewable Energy University of
Blida 1, Blida, Algeria

Cheknane Benamar
Laboratory of Physical Chemistry
of Material Interfaces Applied to
the Environment University of
Blida 1, Blida, Algeria

Hamid Abdelkader
Laboratory of surface and material
treatment
Department of Renewable Energy
University of Blida 1, Blida,
Algeria

Said Noureddine
Associate Professor Department of
Renewable Energy University of
Blida 1, Blida, Algeria

Abstract

Solar desalination is a promising solution for addressing water scarcity in Algeria, using the country's enormous solar energy resources. Desalination technology may produce fresh water in a sustainable and environmentally friendly way by using solar energy. The present work discusses the design and experimental analysis of a linear Fresnel collector with a semi-cylindrical cavity to be employed in a single-stage flash (SSF) desalination plant. The purpose of this study is to investigate the viability and effectiveness of an LFC prototype constructed at Blida University. A simulation study using MATLAB was then carried out. The results revealed that a 5 m² solar array could produce 0.1 kg of distillate per day. The system has a specific thermal energy consumption (STEC) of 308.2 kJ/kg and a gain output ratio (GOR) of 0.7 kg of distilled water per kilogramme of steam.

Keywords

Linear Fresnel collector - SSF plant - solar desalination - freshwater.





2nd National Conference on Green Energy
NCGE'24
15th & 16th December 2024
Boumerdes - Algeria



Paper ID : 34

DFIG-WECS Speed-Sensorless IGBT Open Circuit Fault Optimization Using Fuzzy Sliding Mode Observer

Mokhtar Mahmoud Mohammedi
Laboratory of Electrical Drives
Development (LDEE) of
Electrical Department
University of Sciences and
Technology of Oran Mohamed
Boudiaf Oran, Algeria

Noureddine Messaoudi
LIST Laboratory of
Engineering of Electrical
Systems Department
University M'Hamed
Bougara Boumerdes,
Algeria

Zoubir Gadouche
Laboratory of
Electrical and
Computer
Engineering
(L2GEGI) of
Electrical Department
University Ibn
Khalidun of Tiaret
Tiaret, Algeria

Hocine Guentri
Department of
Mechanic and
Electromechanics,
Institute of Science
and Technologies
Abdelhafid Boussouf
University centre of
Mila, Mila, Algeria

Azeddine Bendiabdellah
Laboratory of Electrical
Drives Development
(LDEE) of Electrical
Department University of
Sciences and Technology
of Oran Mohamed
Boudiaf Oran, Algeria

Nesrine Belabbas
Department of
science and
technology, Institute
of Sciences University
Center Nour Bachir
El bayadh, El
bayadh, Algeria

Abstract

The work presented in this paper deals with Wind Energy Conversion System (WECS) speed-sensorless based on Fuzzy Sliding Mode Observer (FSMO) in Doubly Fed Induction Generator (DFIG) Rotor Side Converter (RSC) IGBT open circuit fault presence. First an indirect power control based on the proportional integral (PI) controller is used and considered as a reference well known approach, then DFIG-WECS speedsensorless using Sliding Mode Observer (SMO) is presented and implemented in the IGBT open circuit fault occurrence. In the aim of optimizing the DFIG-WECS electrical power generation in the fault presence, Fuzzy Sliding Mode Observer (FSMO) is used. The results obtained under MATLAB-Simulink gives value to the FSMO through the faulty condition.

Keywords

Fuzzy Sliding Mode Observer - IGBT open circuit fault - DFIG - WECS - PI controller - MPPT.





2nd National Conference on Green Energy
NCGE'24
15th & 16th December 2024
Boumerdes - Algeria



Paper ID : 39

Improving the Performance of a Hybrid Solar Panel PV/T Using a Solid Corrugated Strip Insert and Water/MWCNT Nanofluid in the Coolant Tubes

Benelhaoues Mohamed
Laboratory of Multiphase Flows and Porous Media
University of Sciences and Technology
Houari Boumedienne FGMGP, BP 32 El Alia 16111 Bab Ezzouar, Algiers, Algeria

Fersadou Brahim
Laboratory of Multiphase Flows and Porous Media
University of Sciences and Technology
Houari Boumedienne FGMGP, BP 32 El Alia 16111 Bab Ezzouar, Algiers, Algeria

Nessab walid
Laboratory of Multiphase Flows and Porous Media
University of Sciences and Technology
Houari Boumedienne FGMGP, BP 32 El Alia 16111 Bab Ezzouar, Algiers, Algeria

Abstract

The hybrid PV/T (Photovoltaic Thermal) system is designed to provide electrical and thermal energy simultaneously. This dual operation reduces the temperature of the photovoltaic cell by extracting heat through the heat transfer fluid. In this way, the overall efficiency of the solar system is increased. This study aims to model a 3D PV/T system in steady state with the integration of a corrugated solid insert inside the tubes. The heat transfer fluid considered is based on the water/MWCNT couple, and the single-phase homogeneous model is used to model the nanofluid flow. To analyze the system performance, a dual energy and exergy analysis was performed. In this study the number of tubes that form the heat exchanger was varied $5 \leq N \leq 25$. The results showed that increasing the number of tubes improves both the thermal and electrical efficiencies with an insignificant penalty in pumping power. From an exergy point of view, an improvement in the quality of electrical energy is obtained at $N=25$, due to the reduction in the temperature of the photovoltaic cells.

Keywords

hybrid solar panel - corrugated strip - nanofluid - coolant tubes - exergy.





Paper ID : 40

Analysis of Low-Frequency Oscillation in Power System with Renewable Energy Sources

Hattabi Intissar
Electrical and control
Department, Faculty
of Technology
Blida 1 University,
Blida, Algeria

Kheldoun Aissa
Laboratory of Signals
and Systems Institute
of Electrical
and Electronic
Engineering
Boumerdes, Algeria

Bradai Rafik
Electronics
Department, Faculty
of Technology
Blida 1 University,
Blida, Algeria

Khettab Soufian
Electrical and control
Department, Faculty
of Technology
Blida 1 University,
Blida, Algeria

Merabet Oussama
Institute of Electrical
and Electronic
Engineering
Boumerdes, Algeria

Mechri Hadjira
Institute of Electrical
and Electronic
Engineering
Boumerdes, Algeria

Abstract

Power systems often experience low-frequency oscillations (LFOs) that, if left unchecked, can lead to instability over time. To mitigate these oscillations, Power System Stabilizers (PSS) are employed through excitation control. In this study, three metaheuristic algorithms—Particle Swarm Optimization (PSO), GOOSE-inspired Optimization Algorithm (GOOSE), and Zebra Optimization Algorithm (ZOA)—were applied for optimal tuning of the tilt-integral-derivation (TID) based PSS parameters in a renewable-integrated multi-machine power system. The results show that ZOA outperformed PSO and GOOSE in enhancing system stability under three phase symmetrical fault.

Keywords

Power system stabilizer - Tilted Integral Derivation Control - small signal stability - Metaheuristic Algorithms.





2nd National Conference on Green Energy
NCGE'24
15th & 16th December 2024
Boumerdes - Algeria



Paper ID : 41

Physical Properties of New Ternary Chalcogenide Copper Molybdate Sulfur I- Cu_2MoS_4

Oum Keltoum NEBEG
Laboratoire de Matériaux application et
valorisation des énergies renouvelable
(LMAVER)
Université Amar Telidji de Laghouat,
Laghouat, Algérie

Mohamed Bouchnafa
Laboratoire de Matériaux application et
valorisation des énergies renouvelable
(LMAVER)
Université Amar Telidji de Laghouat
Laghouat, Algérie

Abde el Nour Benmakhlof
Laboratoire de Matériaux application et
valorisation des énergies renouvelable
(LMAVER)
Université Amar Telidji de Laghouat
Laghouat, Algérie

Abstract

Ternary I- Cu_2MX_4 materials are of great interest because in recent years due their suitable optical and electrical properties and to their different technological application especially solar energy, photocatalysis. In the present work we using ab-initio technic, was carried out to study the structural, electronic properties of the ternary tetragonal I- Cu_2MoS_4 structure. Calculations have been carried out using the plane-wave pseudopotential approach within the framework of the density functional theory (DFT) as implemented in CASTEP code. The calculated structural parameters show a good agreement with the experimental results. The computed partial density of states diagrams, charges transfer and distribution of charge density show that the interatomic bonds are mainly of a covalent nature. Moreover, population analysis is used to check the nature of the chemical bonds. Our DFT calculation indicates that Cu_2MoS_4 compound is a semiconductor with indirect energy band gap of X-G type. In addition to the GGA-PBE, the band structure have been also treated within the nonlocal hybrid functional HSE06. The elastic and optical properties of I- Cu_2MoS_4 were predicted, for the first time, the elastic constants were calculated which exhibits the compounds are mechanically stable by satisfying the condition of stability. Frequency-dependent linear optical parameters are predicted in an energy window from 0 eV to 15 eV for incident electromagnetic radiation polarized parallel to the three principal crystalline directions.as our results show that the studied materials are brittle and are always transparent and shows rather good absorption coefficient in the ultraviolet region.

Keywords

ab initio calculations - Cu_2MoS_4 - semiconductor - structural - electronic properties.





2nd National Conference on Green Energy
NCGE'24
15th & 16th December 2024
Boumerdes - Algeria



Paper ID : 43

Cold Production Using Solar Energy

Nadia Allouache
Department of Process Engineering
University of Science and Technology
Houari Boumediene, USTHB, ALGIERS,
Algeria

Mohamed Belmedani
Department of Process Engineering
University of Science and Technology
Houari Boumediene, USTHB, ALGIERS,
Algeria

Abstract

The numerical modeling and performance prediction of a solid adsorption solar refrigerator, using activated carbon BPL/ammonia adsorbent/adsorbate pair are presented. The mathematical model is based on the thermodynamics of the adsorption process, heat and mass transfers within the adsorbent/adsorbate pair in the refrigerating system.

Keywords

Modeling approach - Refrigeration - Solar energy.





2nd National Conference on Green Energy
NCGE'24
15th & 16th December 2024
Boumerdes - Algeria



Paper ID : 45

Computational Evaluation of Curved Tube Receiver Performance: Comparing Thermo-Hydraulic Impacts of Nanofluids and Conventional Fluids

Tawfiq Chekifi
Unité de Recherche Appliquée en
Energies Renouvelables, URAER
Centre de Développement des
Energies Renouvelables, CDER,
47133, Ghardaïa Algérie

Reski Khelifi
Unité de Recherche Appliquée en
Energies Renouvelables, URAER
Centre de Développement des
Energies Renouvelables, CDER,
47133, Ghardaïa Algérie

Moustafa Boukraa
Research Centre in Industrial
Technologies CRTI
P.O.Box 64, Cheraga 16014,
Algeria

Belaid Abdelfettah
Unité de Recherche Appliquée en
Energies Renouvelables, URAER
Centre de Développement des
Energies Renouvelables, CDER,
47133, Ghardaïa Algérie

Abstract

A three-dimensional numerical analysis of heat transfer in a parabolic through collector's tube receiver, operating with and without nanofluids, was conducted. The study aims to enhance the thermo-hydraulic performance of the absorber tube by increasing fluid turbulence through a wavy internal surface and improving the convective heat transfer coefficient between the heat transfer fluid and the tube receiver wall. Two key factors influencing thermo-hydraulic performance were investigated: the type of working fluid and the internal surface profile of the tube receiver. To achieve this, three heat transfer fluids were examined: water, Therminol VP-1, and Al₂O₃-based thermal oil nanofluid. The simulations employed the RNG $k - \epsilon$ turbulence model, using the finite volume method with ANSYS software. Results indicate that the Nusselt number increased by 3 to 3.5 times for the wavy tube with 2% Al₂O₃-based thermal oil nanofluid compared to a smooth tube. Additionally, the use of nanofluid in a wavy tube enhanced the overall thermo-hydraulic performance by up to 11.19%. Other numerical results, such as pressure drop and temperature variations, were also analyzed and compared with existing empirical and experimental data.

Keywords

Tube receiver - Nanofluid - HTF - Nusselt number and thermo-hydraulic performance.





2nd National Conference on Green Energy
NCGE'24
15th & 16th December 2024
Boumerdes - Algeria



Paper ID : 48

Improved Super-Twisting Sliding Mode Control of twostage PV Grid-Connected Converter

Abdesselam Guerbouz
LAADI Laboratory, Faculty of
Science and Technology
Djelfa University, Algeria

Amine Mehdi Fihakhir
Faculty of Science and Technology
University of Ghardaia, Algeria

Mahdi Taqyedine
LAADI Laboratory, Faculty of
Science and Technology
Djelfa University, Algeria

Djebarni Alaeddine
LAADI Laboratory, Faculty of
Science and Technology
Djelfa University, Algeria

Abstract

The study introduces an Adaptive Super Twisting Sliding Mode (ASTC) technique to enhance the stability and robustness of dc-link voltage in a photovoltaic (PV) gridconnected system. The technique is designed to regulate dc-link voltage quickly and sustain minimal oscillations, ensuring stable operation under dynamic situations. The ASTC's effectiveness is particularly noteworthy in mitigating current total harmonic distortion (THD), which can negatively impact power quality and system efficiency. Comparing the ASTC to conventional control systems, such as Super Twisting and ProportionalIntegral controllers, was conducted using MATLAB/SIMULINK simulations, providing a comprehensive framework for evaluating performance measures across various operating situations.

Keywords

PV - Dc-Link regulator - Super twisting control - THD.





Paper ID : 49

Simulation d'un Système PV/Pile à Combustible avec Stockage pour une Ferme Laitière

Hamida Mohamed Lamine
Department of Electrical
Engineering Electrical
Engineering Advanced
Technology Laboratory
(LATAGE)
Mouloud Mammeri
University, Tizi Ouzou,
Algeria

Cherikh Thiziri
Department of Electrical
Engineering Electrical
Engineering Advanced
Technology Laboratory
(LATAGE)
Mouloud Mammeri
University, Tizi Ouzou,
Algeria

Ait Braham Miliza
Department of Electrical
Engineering Electrical
Engineering Advanced
Technology Laboratory
(LATAGE)
Mouloud Mammeri
University, Tizi Ouzou,
Algeria

Fekik Arezki
Akli Mohand Oulhadj
University, Bouria,
Algeria Ecole centrale de
Nantes, CNRS, LSN, UMR
6004, F-44000, Nantes
France

Denoun Hakim
Department of Electrical
Engineering Electrical
Engineering Advanced
Technology Laboratory
(LATAGE)
Mouloud Mammeri
University, Tizi Ouzou,
Algeria

Résumé

Ce travail porte sur l'étude et la simulation d'un système multi-sources à énergies renouvelables avec stockage pour alimenter une ferme laitière située dans la commune d'IFERHOUNENE. Les systèmes multi-sources combinent plusieurs types de sources afin d'optimiser la production d'énergie. La conception d'une installation multi-sources nécessite une analyse des besoins énergétiques du site, la disponibilité des ressources renouvelables et l'intégration de technologies de stockage d'énergie. En utilisant le logiciel HOMER Pro, nous avons modélisé un système multi source en combinant les sources d'énergie disponibles. La simulation nous a permis d'identifier la configuration la plus efficace pour répondre aux besoins énergétiques de la ferme. Les simulations réalisées ont démontré la faisabilité technique du système proposé dans son ensemble. Enfin, cette approche vise à promouvoir un modèle agricole durable, réduire les coûts énergétiques et diminuer l'empreinte carbone de l'exploitation.

Mots-clés

Système multi-sources - Energies renouvelables - Ferme laitière - Stockage d'énergie - HOMER Pro.





2nd National Conference on Green Energy
NCGE'24
15th & 16th December 2024
Boumerdes - Algeria



Paper ID : 52

Thermogravimetric and Kinetic Analysis of Syagrus Romanzoffiana Fibers for Alternative Renewable Energy Systems

FERFARI Oussama
Department of Mechanical
Engineering, Faculty of
Technology
University 20 August
1955, Skikda, Algeria

HADOU Abdelwaheb
Department of Mechanical
Engineering, Faculty of
Technology
University 20 August
1955, Skikda, Algeria

LALAYMIA Imen
Department of Mechanical
Engineering, Faculty of
Technology
University 20 August
1955, Skikda, Algeria

ABDELLATIF Houssam Eddine
Department of Mechanical
Engineering, Faculty of Technology
University 20 August 1955, Skikda,
Algeria

BELAADI Ahmed
Department of Mechanical
Engineering, Faculty of
Technology
Algeria

Abstract

This study used thermogravimetric analysis to investigate the kinetics and thermodynamics of Syagrus Romanzoffiana fibers (SRFs). We heated SRFs non-isothermally between 25 and 800°C in a nitrogen atmosphere at three different rates: 5°C/min, 10°C/min, and 15°C/min. Thermogravimetric analysis revealed that SRFs pyrolyzed in three phases. The second stage's kinetic and thermodynamic properties have been determined. The low-temperature stable components were decomposed at temperatures ranging from 218 to 376°C, 218 to 391°C, and 218 to 394°C at heating rates of 5°C/min, 10°C/min, and 15°C/min, respectively. The Coats-Redfern approach was used on twenty-one different kinetic models representing four major solid-phase reaction processes. The diffusion model using the Zhuravlev equation is the best-fitted model, with the highest correlation coefficients ($R^2 > 0.99$) across all heating rates. Heating rates of 5, 10, 15, and 20°C/min produced activation energies of 114.02, 118.77, 119.44, and 113.89 kJ/mol, respectively. Thermodynamic properties (ΔH , ΔG , and ΔS) were calculated using kinetic parameters. The data given here contributes to the evaluation of SRFs as a potential biomass renewable energy source for reactor construction and chemical production.

Keywords

Syagrus Romanzoffiana fibers - Thermogravimetric analysis (TGA) - Coats-Redfern method (CRM) - pyrolysis - kinetics - thermodynamics.





2nd National Conference on Green Energy
NCGE'24
15th & 16th December 2024
Boumerdes - Algeria



Paper ID : 54

Effectiveness in the Safety and Security of Energy Systems Case of Risk Management in Electricity Power Plant

Said BELHADJ
Electrical Systems Engineering Department
M'hamed Bouguerra University of Boumedès, Boumerdès, Algeria

Abstract

This article discusses the efficiency of nuclear energy production systems. Significant efforts are being made in the field of nuclear safety and security, which is constantly evolving on a global scale, to promote a safe, scalable, and sustainable development environment aimed at enhancing the protection of people, materials, facilities, nuclear information, and the environment against the harmful effects of radioactivity on human health. Preventive and forward-looking measures must be taken to address potential threats to nuclear assets, such as accidents during operation, use, transportation, theft, sabotage, and the illegal trafficking of nuclear materials and radioactive sources. This article presents nuclear energy as a green energy, based on the efficiency of electronuclear systems and an assessment of the benefits and challenges that remain. Our presentation is based on a structured analysis, with the bibliography carefully selected for the relevance of the articles reviewed and classified according to the main topics identified to support our objective. The article aims to serve as a scientific resource for the choice of green energy, specifically nuclear energy, with a focus on electronuclear energy, while highlighting the central role of security and safety in protecting against nuclear threats and radiological risks in a world transitioning to nuclear energy.

Keywords

Green energy - nuclear energy - electronuclear energy systems - nuclear safety - nuclear security.





Paper ID : 55

A Genetic Algorithm for an Optimum Design in Composite Laminate

Hanane Khouas
Faculty of technology
University m'hamed
bougara boumerdes,
Algeria

Ahmed Tidjani Settet
Faculty of technology
University m'hamed
bougara boumerdes,
Algeria

Abdelkader Nour
Faculty of technology
University m'hamed
bougara boumerdes,
Algeria

Saleh Aguib
Faculty of technology
University m'hamed
bougara boumerdes,
Algeria

Hamza Mechakra
Faculty of technology
University m'hamed
bougara boumerdes,
Algeria

Toufik Djedid
Faculty of technology
University m'hamed
bougara boumerdes,
Algeria

Abstract

Unlike the typical traditional hill-climbing techniques to design a composite laminate. A genetic algorithm code in MATLAB is proposed in this work to optimize of the geometric parameters of laminates panels, treating the following design variables: number of layer, fiber orientation angle and thickness of each layer. The optimization is based on Tsai-Wu criteria and the genetic operators are applied randomly. In order to get the best panels suiting and satisfying the engineer needs. This paper presents the numerical study of the optimization of the geometric parameters of laminates panels , treating the following design variables: number of layer, fiber orientation angle and thickness of each layer. The optimization is based on Tsai-Wu criteria and the genetic operators are applied randomly. A program developed under MATLAB software in order to give the best optimized panel.

Keywords

Design - Genetic Algorithm - composite laminate - optimization - Tsai-Wu.





2nd National Conference on Green Energy
NCGE'24
15th & 16th December 2024
Boumerdes - Algeria



Paper ID : 56

Influence of the Convergent-Divergent Form of the Collector on the Flow Behavior inside A SCPP

DAIMALLAH Ahmed
Laboratoire Energétique, Mécanique et
Ingénieries, Faculty de Technologie
Université M'hamed Bougara de
Boumerdes, Avenue de l'indépendance
35000, Boumerdes Algérie

LEBBI Mohamed
Unité de recherche appliquée en énergies
renouvelables, URAER
Centre de développement des Energies
Renouvelables, CDER,
47133, Ghardaia, Algérie

LOUNICI Mohand Said
Laboratoire Energétique, Mécanique et
Ingénieries, Faculty de Technologie
Université M'hamed Bougara de
Boumerdes, Avenue de l'indépendance
35000, Boumerdes Algérie

Abstract

This work investigates numerical simulation of the effect of the convergent-divergent form of the collector on the flow behaviour in a solar chimney power plant using commercial software Ansys Fluent. The study focuses on the convergent-divergent form of the collector for various positions along the collector Rc^* (3.125, 6.26 and 9.375) and various height of the collector Hc^* (0.125, 0.25, 0.375 and 1) at the convergence position. The momentum and energy equations are solved using finite volume method. A standard $K - \epsilon$ turbulent model is used. Results revealed that the convergent-divergent form of the collector affect sensitively the flow behaviour. We note improvement of mass flow rate by modification of the geometrical form of the collector.

Keywords

Solar chimney - geometrical parameters - CFD - $k - \epsilon$ model - natural convection.





2nd National Conference on Green Energy
NCGE'24
15th & 16th December 2024
Boumerdes - Algeria



Paper ID : 57

Lumped Parameter Thermal Network Model of Three Phase Induction Motor

Mustapha Bouheraoua
Department of electrical Engineering
University Mouloud Mammeri of Tizi
Ouzou, Tizi Ouzou, Algeria

Rabah Khaldi
Department of electrical Engineering
University Mouloud Mammeri of Tizi
Ouzou, Tizi Ouzou, Algeria

Abstract

This paper deals with a Lumped Parameter Thermal Network (LPTN) for the study of the steady-state and transient solution to the temperatures of the 2.2 kW three-phase squirrel cage induction motor. In particular, the thermal model is analyzed by Matlab code software using the analogies existing between the thermal and the electric fields. The model has been verified by means of the experimental test bench, and the temperatures measured have been compared with the simulation results.

Keywords

Induction motor - Lumped parameter - thermal model - Temperature - convection - conduction.





2nd National Conference on Green Energy
NCGE'24
15th & 16th December 2024
Boumerdes - Algeria



Paper ID : 59

Finite Element Analysis of a Tubular Linear Generator for Wave Energy Conversion

Bachir Quartal
Laboratory of Advanced
Technologies in Electrical
Engineering (LATAGE)
Mouloud Mammeri University
Tizi-Ouzou, Algeria

Mustapha Zaouia
Laboratory of Advanced
Technologies in Electrical
Engineering (LATAGE)
Mouloud Mammeri University
Tizi-Ouzou, Algeria

Meziane Hamel
Laboratory of Energy and
Mechanical Engineering (LEMI)
M'Hamed Bougara University
Boumerdes, Algeria

Riad Moualek
Laboratory of Advanced
Technologies in Electrical
Engineering (LATAGE)
Mouloud Mammeri University
Tizi-Ouzou, Algeria

Abstract

In recent decades, the increasing issues of energy deficits and ecological pollution have emerged as significant global challenges. The exploration of innovative technologies for the capture of renewable energy, particularly through wave energy, is considered crucial for addressing these challenges. Among the various solutions, the wave energy converter is recognized as one of the most effective methods for harnessing wave energy. This article delves into the modeling and evaluation of a Wave Energy Harvesting system, which incorporates a tubular linear generator with permanent magnets (TLPMG). This generator operates by converting the kinetic energy generated from the oscillatory motion of sea waves. The developed model relies on the governing equations of the magnetic field, articulated in terms of magnetic vector potential and magnetic scalar potential and is solved using the finite element method. The integration of electromagnetic and mechanical equations is conducted sequentially following the hydrodynamic modeling of the system. The oscillations of the waves are conveyed to the device as vertical displacements. Key findings from this study include the displacement and velocity of the floating buoy, excitation forces, and the resulting electromotive force.

Keywords

Ocean Waves - 3D Finite Element Method - Tubular Linear Permanent Magnet Generators.





2nd National Conference on Green Energy
NCGE'24
15th & 16th December 2024
Boumerdes - Algeria



Paper ID : 60

High Efficiency Photocatalytic Hydrogen Production over Ternary System PANI- MnO_2 - AgBr: Physical, Electrochemical and Optical Properties Studies

Asma Tab
Laboratory of Chromatography,
Faculty of Chemistry
University of Sciences and
Technology Houari Boumediene
(USTHB), Algiers, Algeria

C. Belabed
Laboratory of Materials
Physics, Faculty of Physic
University of Sciences and
Technology Houari
Boumediene (USTHB),
Algiers, Algeria

Mahmut Özacar
Biomaterials, Energy,
Photocatalysis, Enzyme
Technology, Nano and
Advanced Materials,
Additive Manufacturing,
Environmental
Applications and
Sustainability research
and Development group
Sakarya university
Sakarya 54187, Turkey

Mohamed Trari
Laboratory of Storage and
Valorization of Renewable
Energies, Faculty of
Chemistry University of
Sciences and Technology
Houari Boumediene
(USTHB), Algiers, Algeria

Mohammed M.Rahman
Center of Excellence for
Advanced Materials
Research (CEAMR) &
Chemistry department,
Faculty of Science King
Abdulaziz University
Jeddah 21589, Saudi
Arabia

Abstract

The present work explores the enhancement of the hydrogen evolution reaction (HER) through photocatalysis using a novel ternary system, Polyaniline (PANI)- MnO_2 -AgBr. We successfully synthesized by chemical route, the ternary photocatalyst PANI- MnO_2 -AgBr with varying amounts of AgBr (25%, 50%, and 75%). We then investigated the morphology, physical, and electrochemical properties of PANI- MnO_2 @AgBr using X-ray diffraction and UV-visible spectroscopy. Semi conductivity was demonstrated through capacitance measurements, which revealed flat band potentials ($E_{fb} = 0.90, 0.86, \text{ and } 0.33 \text{ V SCE}$) and carrier concentrations ($1.681021, ND = 4.54 \cdot 10^{17} \text{ and } 1.38 \cdot 10^{18} \text{ cm}^{-3}$) for PANI, MnO_2 , and AgBr, respectively. Regarding the hydrogen production, a comparative study between PANI- MnO_2 -AgBr 25% and other prepared photocatalyst was conducted. PANI- MnO_2 -AgBr 25% exhibited the highest hydrogen evolution reaction (HER) performance, achieving a quantum yield of 1.53% and a release rate of $159.51 \mu\text{mol/g min}^{-1}$. Notably, the photocatalytic activity was fully recovered after three successive cycles, showing no signs of deactivation, which indicates the catalyst's excellent reusability across multiple cycles.

Keywords

Hydrogen evolution reaction (HER) - PANI - MnO_2 AgBr - Photocatalyst - Reusability - Energy production.





2nd National Conference on Green Energy
NCGE'24
15th & 16th December 2024
Boumerdes - Algeria



Paper ID : 62

Integration of Biomass Energy into the Essential Oil Extraction Process

Amina Ben Bouabdallah
Faculty of Technology, Process
Engineering Department
M'hamed Bougara university of
Boumerdes, Boumerdes, Algeria

Benalia Kouini
Faculty of Technology, Process
Engineering Department
M'hamed Bougara university of
Boumerdes, Boumerdes, Algeria

Farid Zemoul
Faculty of Technology, Process
Engineering Department
M'hamed Bougara university of
Boumerdes, Boumerdes, Algeria

Nassima Boufellah
Faculty of Technology, Process
Engineering Department
M'hamed Bougara university of
Boumerdes, Boumerdes, Algeria

Abstract

Agro-industrial processes that utilizes aromatic and medicinal plants generates various kinds of residues like residual biomasses from distillation of aromatic plant and non-utilized parts of medicinal plant. These residual biomasses cannot be considered as waste as these can actually be recycled and converted into value added products. Nevertheless, the energy potential of this waste is interesting and their integration as energy inputs in industrial processes has considerable economic and environmental stakes. These wastes can be used as fuel for production of steam necessary for the extraction of essential oils (EO) by hydrodistillation (HD). In this study, hydrodistillation extraction process using biomass as an energy source (BEHD) was applied for the extraction of essential oil from a plant from the Mediterranean region. The results obtained in terms of yield and extraction time were compared with those obtained by the conventional method using electric heating. The antimicrobial activity of the EO was evaluated against four bacteria and one pathogenic yeast, using the disc-diffusion method and minimal inhibitory concentration (MIC), whereas, the antioxidant activity of the EO was evaluated using the DPPH test. The results obtained showed that the EO extracted by BEHD have faster kinetics and higher efficiency with similar yields: 1.03% and an extraction time of 30 min against 180 min for classic hydrodistillation. In addition, the oil extracted by BEHD has a better antioxidant activity and it is much more active than that isolated by HD.

Keywords

biomass - energy - essential oil - extraction - aromatic and medicinal plant.





2nd National Conference on Green Energy
NCGE'24
15th & 16th December 2024
Boumerdes - Algeria



Paper ID : 63

Fractal Dimension as a Diagnostic Tool for Signal Analysis in Polluted High-Voltage Insulators

Imene Ferrah
Laboratoire de Recherche en
Electrotechnique, Ecole Nationale
Polytechnique d'Alger
10 Avenue Hassen Badi, B.P 182,
El-Harrach, 16200 Algiers, Algeria

Madjid Tegar
Laboratoire de Recherche en
Electrotechnique, Ecole Nationale
Polytechnique d'Alger
10 Avenue Hassen Badi, B.P 182,
El-Harrach, 16200 Algiers, Algeria

Abstract

This study presents the implementation of a multi-resolution algorithm based on the box-counting method to calculate the fractal dimension (FD) of various electrical signals, including leakage current and electrical load, recorded from a high-voltage flat insulator model exposed to pollution. The algorithm was validated using fractal parametric signals with known theoretical fractal dimensions, particularly the Weierstrass function (WF), showing strong agreement with theoretical values and a relative error of less than 2%. After validation, the algorithm was applied to the leakage current and load signals to evaluate the effectiveness of FD in describing insulator performance and identifying the most diagnostic signal under uniform and non-uniform pollution conditions. Results indicated that for uniform pollution, the FD of the leakage current increases with pollution conductivity, rising quickly at low conductivities and stabilizing at higher levels. In non-uniform pollution, the FD also increased with width and conductivity, with the highest values observed when pollution was on the high-voltage side. The FD of the electric load signal remained mostly unaffected by uniform pollution but showed increases in discontinuous pollution, highlighting its potential as a diagnostic tool for assessing the surface condition of polluted insulators.

Keywords

Fractal - leakage current - box counting method - HV insulator model.





2nd National Conference on Green Energy
NCGE'24
15th & 16th December 2024
Boumerdes - Algeria



Paper ID : 65

Enhanced Secondary Control Design for Three Phase VSI-based Microgrids

Camelia Ait Hammouda
LATSI Laboratory, dept.
Of Renewable Energies
Blida 1 University Blida
09000, Algeria

Ahmed Bendib
SET Laboratory, dept. of
electronics
Blida 1 University Blida
09000, Algeria

Rafik Bradai
LATSI Laboratory, dept.
Of electronics
Blida 1 University Blida
09000, Algeria

Abdelhammid Kherbachi
Wind Energy Division
Center of
Renewable Energy
Development Bouzareah,
Algiers, Algeria

Rachid Boukenoui
SET Laboratory, dept. of
Renewable Energies
Blida 1 University Blida
09000, Algeria

Abstract

Microgrids (MGs) have become increasingly important in recent years for integrating Distributed Generation (DG) sources, energy storage systems, and controllable loads into low- and medium-voltage networks. These systems, often powered by Renewable Energy Sources (RESs) like solar and wind, are managed using a hierarchical control structure. At the primary control level, the focus is on balancing power among multiple converters while keeping voltage and frequency stable. However, deviations in these parameters can still occur, requiring secondary control to correct and restore them to their nominal values. This paper introduces a secondary control method based on Double Enhanced Second Order Integrator Frequency Locked Loop (DESOGI-FLL), aimed at enhancing DC offset rejection and improving performance in MG systems. The proposed approach addresses gaps in parameter tuning and control design for greater system stability.

Keywords

Three-Phase Microgrid - Photovoltaic System - Secondary Control - Restoration - synchronization.





2nd National Conference on Green Energy
NCGE'24
15th & 16th December 2024
Boumerdes - Algeria



Paper ID : 66

Experimental Implementation of Fuzzy Logic Based Energy Management for Horizon PEM Fuel Cell/Ultra Capacitor System

Haroune Aouzellag
Laboratoire de Maitrise des Energies
Renouvelables, Faculté de Technologie
Université de Bejaia, Bejaia, Algeria

Bessam Amrouche
Laboratoire de Maitrise des Energies
Renouvelables, Faculté de Technologie
Université de Bejaia, Bejaia, Algeria

Meziane Hamel
Département d'ingénierie des systèmes
électriques, Faculté de Technologie
Université de Boumerdes, Boumerdes,
Algeria

Abstract

This paper presents an experimental implementation of an energy management strategy for fuel cell vehicle based on fuzzy logic control (FLC) for a Horizon PEM fuel cell assisted with an ultra-capacitor (UC). The UC cells are MAXWELL technology. The FLC is an online technique to optimize the energy flows between different sources in aim to minimize fuel consumption and maintain the state of charge of storage sources. To respect the dynamics of the fuel cell, a filter is added to the output of the FLC. The sources are chosen to increase the system's energy autonomy using Ragon diagram. All controls are implemented using dSpace 1005 board and the results show the effectiveness of those controls by respecting the dynamic of the fuel cell and maintaining the constraints control on the desired limits.

Keywords

Energy management - ultra capacitor - battery - fuel cell - vehicle - fuzzy logic.





2nd National Conference on Green Energy
NCGE'24
15th & 16th December 2024
Boumerdes - Algeria



Paper ID : 67

Passivity-Based Control Approach for Electric Vehicle Optimization

Bessam Amrouche
Laboratoire de Maitrise des
Energies Renouvelables, Faculté de
Technologie Université de Bejaia,
Bejaia, Algeria

Nacef Sabrina
Laboratoire de Maitrise des
Energies Renouvelables, Faculté de
Technologie Université de Bejaia,
Bejaia, Algeria

Haroune Aouzellag
Laboratoire de Maitrise des
Energies Renouvelables, Faculté de
Technologie Université de Bejaia,
Bejaia, Algeria

Koussaila Iffouzar
Laboratoire des Sciences
Appliquées
Ecole Nationale Supérieure des
Technologies Avancées, ENSTA
d'alger, Algiers

Abstract

This study presents a hybrid energy system designed to supply a Permanent Magnet Synchronous Machine (PMSM) through the integration of a fuel cell and a supercapacitor, functioning as the primary and secondary power sources, respectively. The fuel cell serves as the main energy provider, delivering a steady baseline power, while the supercapacitor is employed to manage rapid load variations and supply peak power demands. This configuration leverages the complementary properties of each source: the fuel cell offers high energy density for sustained operation, while the supercapacitor provides high power density and rapid response capabilities, ideal for handling transient loads. The system's energy management is facilitated by a power electronic converter, which regulates the power distribution between the fuel cell and supercapacitor based on real-time load requirements. A control strategy has been developed to optimize fuel cell operation within its efficient operating range, thereby reducing stress on the fuel cell and extending its lifespan. This control strategy prioritizes supercapacitor discharge during high-demand periods, effectively buffering the fuel cell from sudden load changes, which could otherwise degrade its performance and efficiency. Such a hybrid system is particularly suited for applications requiring both reliability and flexibility in power delivery, such as electric vehicles, renewable energy integration, and remote power systems. By combining fuel cell sustainability with supercapacitor agility, this system achieves improved energy efficiency, extended component lifespan, and enhanced dynamic performance under variable load conditions. The findings from this research contribute to the design of more resilient and efficient power systems in advanced electromechanical applications.

Keywords

Energy management - ultra capacitor - fuel cell - vehicle - IDA-PBC.





2nd National Conference on Green Energy
NCGE'24
15th & 16th December 2024
Boumerdes - Algeria



Paper ID : 68

Thermal Performance of Wavy Channel Heat Exchange

Abderrahmane Mezaache
Laboratoire de Génie Mécanique et
Matériaux, LGMM, Department of
Mechanical Engineering, Faculty of
Technology University of Skikda, Algeria

Fateh Mebarek-Oudina
Department of Physics, Faculty of Sciences
University of Skikda, Algeria

Abstract

Scientific investigations on heat exchangers are mainly utilized to build and enhance new engineering systems with higher thermal efficiency. The most attractive approaches to accomplish this objective are passive methods using nanofluids, fins, porous media and wavy walls. The present study emphasizes heat transfer in a nanofluid laminar flow within a wavy canal partially occupied by porous material. The physical modeling relies on the two-dimensional laminar formulation of Darcy-Brinkman-Forchheimer (DBF) and the local thermal equilibrium model (LTE). Numerical solutions are acquired based finite volume using Ansys Fluent software method. Furthermore, the numerical results are validated with previous works. The simulations are achieved for AISI 304 porous medium and CuO-water nanofluid. The combined effects of porous layer thickness and Reynolds number on heat transfer and temperature contours are explored and illustrated. The simulation results demonstrate that a porous layer insert can enhance heat transfer in clear wavy channels. The findings hold potential implications for diverse applications, ranging from advanced cooling systems to energy-efficient industrial processes.

Keywords

porous medium - heat transfer - wavy wall - nanofluid - entropy generation.





2nd National Conference on Green Energy
NCGE'24
15th & 16th December 2024
Boumerdes - Algeria



Paper ID : 70

Assessing the Role of Solar Irradiance Parameters in WRF Simulations: Implications for Climate Modeling and Renewable Energy Applications

BAHLOULI Abdelhak
Theoretical Physics Laboratory, A. Mira University of Bejaia, Algeria
Targua Ouzemour Campus, Bejaia 06000, Algeria, University of Bejaia
Targua , Algeria

Abstract

This study explores the pivotal role of solar irradiance parameters in the Weather Research and Forecasting (WRF) model, emphasizing their significance in climate modeling and renewable energy applications. By evaluating key parameters such as downward shortwave radiation flux (SWDOWN), Direct Normal Irradiance (DNI), and Global Horizontal Irradiance (GHI), this research provides insights into how these factors influence solar energy availability and atmospheric dynamics. The analysis highlights the intricate interactions between solar radiation, atmospheric conditions, and surface properties, including the effects of aerosol optical depth (AOD) and cloud cover on solar irradiance levels. The study further investigates the implications of accurate solar irradiance modeling for climate projections and energy resource assessments, underscoring the importance of precise parameterization in WRF simulations. Results demonstrate that improved understanding and representation of solar irradiance parameters can enhance the predictive capabilities of climate models, ultimately facilitating more effective planning and optimization of renewable energy strategies. This research contributes to the advancement of both meteorological forecasting and sustainable energy solutions by integrating solar irradiance assessments into WRF simulations.

Keywords





2nd National Conference on Green Energy
NCGE'24
15th & 16th December 2024
Boumerdes - Algeria



Paper ID : 71

Evaluating Power Control Techniques for DFIGWT: A Comparison of Direct, Fuzzy Direct, and Indirect Control Methods

Zoubir Gadouche
Laboratory of Electrical and Computer
Engineering (L2GEGI) of Electrical
Department University Ibn Khaldun of
Tiaret Tiaret, Algeria

Mokhtar Mahmoud Mohammedi
Laboratory of Electrical Drives
Development (LDEE) of Electrical
Department University of Sciences and
Technology of Oran Mohamed Boudiaf
Oran, Algeria

Noureddine Messaoudi
LIST Laboratory of Engineering of
Electrical Systems Department
University m'hamed bougara boumerdes

Abstract

This study evaluates three power control strategies for DFIG wind turbines (DFIG-WT), Indirect Power Control (IPC), Direct Power Control (DPC), and Fuzzy Direct Power Control (FDPC), with a focus on energy quality and response time. Using Simulink MATLAB for simulation, the study compares each strategy's performance in maintaining high-quality energy output and its response time to fluctuations. IPC is effective in decoupling power control, offering stable energy quality with slightly longer response times. DPC is highlighted for its simplicity and rapid response but may compromise on energy quality under dynamic conditions. FDPC, utilizing fuzzy logic, demonstrates superior handling of uncertainties, improving energy quality and maintaining reasonable response times. The results reveal distinct trade-offs among these strategies, providing valuable insights for selecting the optimal control approach based on desired energy quality and response time.

Keywords

Fuzzy Direct Power Control (FDPC) - Indirect Power Control (IPC) - DFIG wind turbines - Energy quality - Response time.





2nd National Conference on Green Energy
NCGE'24
15th & 16th December 2024
Boumerdes - Algeria



Paper ID : 77

Enhancing Electric Power Quality of AWPS by Modified Bridgeless SEPIC PFC Converter

N. Hamouda
Research Center in
Industrial Technologies
CRTI
P.O. Box 64, Cheraga
16014, Algiers, Algeria

M. Haddad
Research Center in
Industrial Technologies
CRTI
P.O. Box 64, Cheraga
16014, Algiers, Algeria

B. Lekouaght
Research Center in
Industrial Technologies
CRTI
P.O. Box 64, Cheraga
16014, Algiers, Algeria

B. Babes
Research Center in
Industrial Technologies
CRTI
P.O. Box 64, Cheraga
16014, Algiers, Algeria

N. Cherrat
M'hamed Bougara
Boumerdes University
Faculty of Technology

Abstract

This paper introduces an efficient bridgeless power factor corrected (PFC) modified single-ended primary inductor converter (SEPIC) tailored for arc welding power supplies (AWPS). The proposed system features two key components. In grid side, a modified bridgeless SEPIC PFC converter, managed by a PI controller to ensure a high power factor and quick response, and in welding circuit side, a full bridge buck converter with a high-frequency transformer (HFT) to provide isolation, enhancing stability during welding. Simulations of the configuration and controllers are carried out across various operating conditions typical of AWPS. The system's performance is evaluated using power quality indicators, including power factor (PF), total harmonic distortion (THD) of the AC grid current, and voltage regulation. Findings indicate that the proposed design improves weld bead quality by delivering a steady output current and maintaining arc stability, aligning with international power quality standards and providing robust voltage regulation.

Keywords

Arc welding power supply (AWPS) - bridgeless PFC converter - modified single ended primary inductor converter (SEPIC) - PI controller.





2nd National Conference on Green Energy
NCGE'24
15th & 16th December 2024
Boumerdes - Algeria



Paper ID : 78

Performance Enhancement of DC-DC Boost Converter Using PSO-Optimized PI Controller

Ratiba Fellag
Robotics and Industrial Automation
Laboratory
Centre de Développement des Technologies
Avancées (CDTA), Algiers, Algeria

Mahmoud Belhocine
Robotics and Industrial Automation
Laboratory
Centre de Développement des Technologies
Avancées (CDTA), Algiers, Algeria

Meziane Hamel
LEMI Laboratory of Energy and
Mechanical Engineering
M'Hamed Bougara University, (UMBB),
Boumerdes, Algeria

Abstract

This paper presents an effective approach to enhancing the closed-loop control of boost converters using Proportional-Integral (PI) control optimized by Particle Swarm Optimization (PSO). Boost converters are crucial components in various power electronics applications, and their performance significantly depends on the efficacy of the control system. While PI controllers are widely used due to their simplicity and reliability, tuning them for optimal performance remains challenging. The PSO algorithm iteratively searches for the optimal combination of proportional and integral gains, aiming to minimize settling time, overshoot, and steady-state error while maximizing the overall system stability. The proposed method is validated through simulation experiments.

Keywords

Boost converter - PI - PSO - optimal tuning.





2nd National Conference on Green Energy
NCGE'24
15th & 16th December 2024
Boumerdes - Algeria



Paper ID : 79

Application of Artificial Neural Networks for the Modeling of a Dual Fuel Diesel Engine Powered by Different Hydrogene Fractions

M. A. Benbellil
Laboratoire LEMI, Faculty of
Technology
University of M' Hamed Bougara,
Boumerdes 35000, Algeria

N. MOUGARI
Laboratoire LEMI, Faculty of
Technology
University of M' Hamed Bougara,
Boumerdes 35000, Algeria

D. GHERSI
Laboratory of Theoretical and Applied
Fluid Mechanics, Faculty of Physics
University of Science and Technology
Houari Boumediene, BP 32 Bab Ezzouar,
16111, Algiers, Algeria

M. S. LOUNICI
Laboratoire LEMI, Faculty of
Technology
University of M' Hamed Bougara,
Boumerdes 35000, Algeria

Abstract

With dwindling oil reserves and environmental concerns about exhaust emissions from conventional diesel, attention is increasingly turning to alternative fuels such as hydrogen (H_2). Dual-fuel (DF) operation is an interesting technique both economically and environmentally. Artificial neural networks (ANNs) allow complex problems to be modeled and solved using structures inspired by the human brain, enabling artificial intelligence to perform tasks such as predicting outcomes. This paper presents the development of models using the ANN approach to predict both the effective efficiency (BTE), specific consumption (BSEC) and diesel energy of a DF diesel engine fuelled by different H_2 fractions. The input parameters of the models are effective power (BP) and H_2 (hydrogen), while engine efficiency (BTE), specific energy consumption (BSEC) and diesel energy are the output parameters. The data set showed maximum R values for the prediction of performance parameters (BTE, BSEC, Diesel Energy). The R values indicate that 99% of the total variation was identified and explained by the ANN model, and corresponds to the experimental data. These results highlight the reliability of the artificial neural network approach, offering high predictive capability, thanks to its speed and learning power.

Keywords

Dual fuel - Diesel engine - Prediction - Artificial neural network - Performance; Emissions.





Paper ID : 80

Prediction and Optimization of Performance Parameters and Emissions Characteristics of a Diesel Engine Fueled by Castor Oil-Based Biodiesel

M. A. Benbellil
Laboratoire LEMI, Faculty of
Technology
University of M' Hamed Bougara,
Boumerdes 35000, Algeria

N. MOUGARI
Laboratoire LEMI, Faculty of
Technology
University of M' Hamed Bougara,
Boumerdes 35000, Algeria

D. GHERSI
Laboratory of Theoretical and Applied
Fluid Mechanics, Faculty of Physics
University of Science and Technology
Houari Boumediene, BP 32 Bab Ezzouar,
16111, Algiers, Algeria

M. S. LOUNICI
Laboratoire LEMI, Faculty of
Technology
University of M' Hamed Bougara,
Boumerdes 35000, Algeria

Abstract

In view of the declining oil reserves and the adverse environmental consequences of petroleum diesel exhaust, biodiesel has attracted attention as a renewable and environmentally friendly fuel. This work presents the development of models based on the artificial neural network (ANN) approach, for the prediction of performance parameters and emission characteristics of a diesel engine operating with a blend of biodiesel extracted from castor oil, as well as the optimization of the thermal efficiency of the engine using the genetic algorithm (GA). The engine load and the diesel and biodiesel blend ratio were considered as input parameters for the models, while the performance parameters which are effective thermal efficiency (BTE), specific energy consumption (BSEC), fuel mass flow rate (Fuel mass), exhaust gas temperature (EGT) and excess air ratio were considered as input parameters of the first model. The emission characteristics which are carbon monoxide (CO), hydrocarbons (HC) and nitrogen oxides (NO_x) are the output parameters of the second model. The results showed a good correlation between the experimental values and the predicted values. The performance analysis showed that the accuracy of the models is very high. The dataset provided maximum linear correlation coefficient (R) values of 0.99838 for performance parameter prediction and 0.97584 for emission prediction. The integration of GA with ANN was able to optimize the best combination of diesel-biodiesel blend ratio and engine load for maximum effective thermal efficiency. These results reveal that the ANN-based approach is robust with high predictive power to predict the performance parameter and emission characteristics parameters of a diesel engine running on castor oil biodiesel blend, due to its combination of speed and learning ability.

Keywords

Genetic algorithm - Biodiesel - Diesel engine - Prediction - Artificial neural networks - Optimization.





Paper ID : 81

Simulation de la Dégradation de Performance Électrique d'un Module Photovoltaïque avec Fissuration

R. Doumane
Université M'Hamed Bougara, LEMI
avenue de l'Indépendance, 35000
Boumerdès, Algérie

A. Ennemri
Université M'Hamed Bougara, LEMI
avenue de l'Indépendance, 35000
Boumerdès, Algérie

P.O Logerais
Université Paris-Est, CERTES, IUT de Sénart
rue Georges Charpak, 77567 Lieusaint, France

Résumé

Les performances des modules photovoltaïques sous conditions réelles sont assez différentes que celles déterminées sous conditions de laboratoire pendant la qualification ou la certification. Cette différence est due au fait que les systèmes PV sont très sensible aux conditions climatologiques de site d'installation : rayonnement solaire, température, pression, humidité, vitesse du vent, pluviométrie, . . . , etc. En simulant ces phénomènes, on évalue leur effet sur les propriétés électriques du module, notamment la production de courant et la tension en fonction de l'irradiation solaire. Pour étudier l'influence de la fissuration sur une cellule PV, une analyse des performances électriques a été faite. La simulation de la dégradation de performance électrique d'un module photovoltaïque avec fissuration consiste à modéliser l'impact des fissures sur l'efficacité de conversion de l'énergie solaire en électricité. La simulation numérique sous MATLAB de la fissuration des cellules PV a permis d'estimer la dégradation des performances d'un module photovoltaïque et les résultats montrent que la dégradation du courant I_{cc} et de la puissance maximale P_{max} est linéaire. le courant de court-circuit I_{cc} chute de manière significative par rapport à la tension en circuit ouvert V_{co} et de même pour la puissance maximale P_{max} . Ainsi une altération de la surface par fissuration de 79% donne une perte de puissance de 24 à 25%.

Mots-clés

Système photovoltaïque - dégradation - modélisation - fissuration - performances électriques.





2nd National Conference on Green Energy
NCGE'24
15th & 16th December 2024
Boumerdes - Algeria



Paper ID : 82

Numerical Study of Thermal Efficiency Ventilated Cavity Using the LBM-MRT

Nabil Himrane
Department of Mechanical
Engineering, Faculty of Technology
University M'hamed Bougara of
Boumerdes, Algeria

Assia Arab
Department of Mechanical
Engineering, Faculty of Technology
University M'hamed Bougara of
Boumerdes, Algeria

Djamel Eddine Ameziani
Department of Mechanical
Engineering, Faculty of Technology
University M'hamed Bougara of
Boumerdes, Algeria

Zouhira Hireche
Department of Mechanical
Engineering, Faculty of Technology
University M'hamed Bougara of
Boumerdes, Algeria

Abstract

This study delves into a numerical study of thermal comfort in the residential buildings using the Lattice Boltzmann method (LBM). The research aims to enhance indoor air quality, ventilation efficiency and thermal comfort. The physical model considered consists of a rectangular cavity, characterized by an aspect ratio of two and ventilated by two diagonally opposite openings. The system of equations was solved using the Lattice Boltzmann method with multiple relaxation times (LBM-MRT). The extended Darcy Brinkman-Forchheimer model was used to simulate the porous material. The influence of different control parameters, including Rayleigh, Reynolds, and Darcy numbers, on flow dynamics, heat transfer and mass transfer was analyzed. The results reveal that the reactive porous partition significantly boosts thermal efficiency with peak performance achieved at specific permeability and partition heights. These findings offer essential insights for the design of advanced ventilation systems, ultimately contributing to improved indoor environmental quality.

Keywords

Thermal comfort - displacement ventilation - LBM-MRT.





2nd National Conference on Green Energy
NCGE'24
15th & 16th December 2024
Boumerdes - Algeria



Paper ID : 83

Enhancing the Quality of Electrical Energy Generation in Wind Energy Conversion Systems Using Robust Sliding Mode Control

Nidhal CHERRAT
Dept. of Electrical
Systems Engineering
ISE University of
Boumerdes
Laboratoire
d'Automatique de
Jijel-LAJ, University
MSBY of Jijel

Mohamed KAOUANE
Dept. of Electrical
Systems Engineering
ISE
University of
Boumerdes
Boumerdes, Algeria

Badis LEKOUAGHET
Research Center in
Industrial Technologies
(CRTI)
Algiers, Algeria

Mohammed HADDAD
Research Center in
Industrial Technologies
(CRTI)
Algiers, Algeria

Hamid BOUBERTAKH
Department of
Automatique University
MSBY of Jijel
Laboratoire
d'Automatique de
Jijel-LAJ, University
MSBY of Jijel, Jijel,
Algérie

Amina BOUNAR
of Automation
Faculty of Electrical
Engineering
Houari-Boumediene
University of Science
and Technology
(USTHB), Algiers,
Algeria

Abstract

This paper investigates the improvement of the electrical energy production in wind energy conversion systems by applying a robust control strategy to a doubly fed induction generator (DFIG). This system presents significant control challenges due to its dynamic equations are highly non-linear, coupled, and complex. In this strategy, a sliding mode controller (SMC) is used in the vector control to avoid the drawbacks of using the proportional-integral (PI) compensator and improve the closed-loop control performance, such as steady state error, robustness against perturbations, and transient response. A simulation study is presented to demonstrate the performance of the proposed control scheme against the conventional vector control scheme that based on a PI compensator.

Keywords

Wind energy conversion systems - doubly fed induction generator - sliding mode controller (SMC) - vector control - proportional-integral (PI) compensator.





2nd National Conference on Green Energy
NCGE'24
15th & 16th December 2024
Boumerdes - Algeria



Paper ID : 84

Design and Implementation of a DC-DC boost converter for a Photovoltaic Water Pumping System

Riad Moualek
Laboratory for
Advanced
Technologies in
Electrical Engineering
(LATAGE) University
Mouloud Mammeri of
Tizi-Ouzou, Algeria

Meziane Hamel
Laboratory of Energy
and Mechanical
Engineering (LEMI)
University M'Hamed
Bougara of
Boumerdes

Mohamed Kaouane
Department of
Electrical Systems
Engineering
University M'Hamed
Bougara of
Boumerdes

Lutu Stephen Gonzaga
University M'Hamed
Department of Electrical
Systems Engineering
Bougara of Boumerdes

Allal Cherif Mohamed
Department of
Electrical Systems
Engineering
University M'Hamed
Bougara of
Boumerdes

Ahmed Nait Ouslimane
University Mouloud
Department of
Electrotechnics
Mammeri of Tizi-Ouzou

Abstract

This work focuses on the design and implementation of a DC-DC boost converter for a Photovoltaic Water Pumping System (PVWPS). We propose an innovative DC-DC booster designed to enhance the overall efficiency of photovoltaic energy generation in standalone applications. The proposed booster distinguishes itself with reduced switching losses, attributed to the integration of the IR2110 driver, streamlined command simplicity, and minimized circuit congestion compared to existing solutions. This system is engineered to convert a 30V DC input from solar panels into a variable DC output, crucial for powering one of the water fountains at our faculty across varying water heads.

Keywords

DC-DC boost converter - PVWPS - Electronic Card Design - Solar panels.





Paper ID : 85

Modeling Biohydrogen Production from Organic Wastes via Dark Fermentation using Artificial Neural Networks

Nour Elislam MOUGARI
Laboratory of Energy,
Mechanics and
Engineering Mechanical
Engineering Departement
Faculty of Technology,
University Mhamed
Bougara Boumerdes,
Boumerdes, Algeria

Djamal Eddine GHERSI
Energy and Fluid
Mechanics Department
Laboratory of
Theoretical and Applied
Fluid Mechanics
University of Science
and Technology Houari
Boumediene, Algiers,
Algeria

Nabil HIMRANE
Laboratory of Energy,
Mechanics and
Engineering
Mechanical
Engineering
Departement Faculty
of Technology,
University Mhamed
Bougara Boumerdes,
Boumerdes, Algeria

Hanane CHERADI
Laboratory of Energy,
Mechanics and
Engineering
Mechanical
Engineering
Departement Faculty
of Technology,
University Mhamed
Bougara Boumerdes,
Boumerdes, Algeria

Abdelali Messaoud BENBELLIL
Laboratory of Energy, Mechanics
and Engineering Mechanical
Engineering Departement
Faculty of Technology, University
Mhamed Bougara Boumerdes,
Boumerdes, Algeria

Madjid HACHEMI
Laboratory of Energy,
Mechanics and
Engineering
Mechanical
Engineering
Departement Faculty
of Technology,
University Mhamed
Bougara Boumerdes,
Boumerdes, Algeria

Abstract

The growing focus on sustainable energy has spurred interest in biohydrogen production through dark fermentation of organic waste. This approach offers the dual advantages of clean energy generation and effective waste management. However, optimizing the process remains challenging due to the complex interactions between substrate composition, microbial activity, and fermentation parameters. This study presents a modeling approach for biohydrogen production from organic wastes via dark fermentation using Artificial Neural Networks (ANN). Data from 10 published works were compiled to develop the model, with input variables including substrate type, temperature, pH, and substrate concentration, and biohydrogen yield as the output variable. The ANN model demonstrated high predictive performance, showing a strong correlation between predicted and experimental data, as evidenced by high R^2 value of 0.9977. This indicates the model's robustness and reliability in capturing the complex relationships governing biohydrogen production. By leveraging data from the literature, the study underscores the potential of ANN as a powerful tool for optimizing biohydrogen production processes, facilitating a deeper understanding of the key parameters influencing yield. This work provides valuable insights into the use of machine learning in renewable energy research and highlights the prospects of dark fermentation as a sustainable pathway for biohydrogen production.

Keywords

Artificial Neural Networks (ANN) - Biohydrogen - Dark fermentation - Organic wastes - Prediction.





2nd National Conference on Green Energy
NCGE'24
15th & 16th December 2024
Boumerdes - Algeria



Paper ID : 86

Effet de la Richesse sur des Flammes de Méthane Hydrogène

Sofiane Ouali
Laboratoire d'Énergétique, de Mécanique et d'Ingénierie (LEMI)
Faculté de Technologie, Université M'Hamed Bougara (UMBB),
Boumerdes, Algérie

Résumé

Cette étude présente les résultats de simulations numériques examinant l'influence de la richesse sur un mélange réactif composé d'air, de méthane (CH_4) et d'hydrogène (H_2), avec des concentrations de 50% – 50% pour le CH_4 et H_2 . La richesse a été variée de 0.45 à 1 avec un pas de 0.5. Ces simulations ont été réalisées sur un brûleur haute pression, conçu pour une utilisation dans les turbines à gaz, opérant à une pression d'injection de 3 bars délivrant ainsi une puissance avoisinant 120 kW. Les résultats de simulation révèlent des variations substantielles étroitement liées à l'augmentation de la richesse mélange réactif. Ces derniers revêtent une importance significative pour la compréhension des performances et de la stabilité de tels brûleurs dans des conditions de haute pression, avec des implications potentielles dans les domaines de la combustion industrielle et de la production énergétique par turbines à gaz fonctionnant avec $CH_4 - H_2$.

Mots-clés

Combustion - Pré-mélange - Hydrogène - Méthane - CFD - Ecoulement réactif - Turbulence - Polluants.





Paper ID : 87

Simulation Numérique de la Combustion du CH_4 Enrichi au H_2

Sofiane Ouali
Laboratoire d'Énergétique, de Mécanique et d'Ingénierie (LEMI)
Faculté de Technologie, Université M'Hamed Bougara (UMBB),
Boumerdes, Algérie

Résumé

La combustion flamme-less constitue un régime de combustion innovant du point de vue des émissions polluantes et de la consommation de combustible. Ce mode de combustion se caractérise fréquemment par des zones de réaction uniformément distribuées, susceptibles de réduire les gradients de température, les oscillations acoustiques et par conséquent, la génération de NO_x . La technologie de combustion sans flamme a démontré sa capacité d'adaptation à l'utilisation de combustibles conventionnels. Cependant, il s'avère nécessaire d'évaluer les performances des équipements thermiques industrielles lors de l'utilisation de combustibles alternatifs produits à partir de ressources renouvelables. L'hydrogène représente l'une des alternatives les plus prometteuses. Ce travail présente une étude numérique porte sur l'effet de l'utilisation d'un mélange $CH_4 - H_2$ comme combustible dans un brûleur à jet dans un écoulement coaxial chaud et de l'influence de la température d'entrée de l'air sur les émissions polluantes. L'étude a été menée pour 5 concentrations différentes de H_2 (de 5% à 30% avec un pas de 5%) et 7 températures d'entrée d'air (de 300 K à 900 K avec un pas de 100 K). Les résultats ont mis en évidence une diminution des NO_x et de CO en fonction de l'augmentation en teneur du H_2 .

Mots-clés

Combustion - Pré-mélange - Hydrogène - Méthane - CFD - Ecoulement réactif - Turbulence - Polluants.





2nd National Conference on Green Energy
NCGE'24
15th & 16th December 2024
Boumerdes - Algeria



Paper ID : 88

Improving Power Quality and Dynamic Performance of Modular Multilevel Converter based Microgrid Solar System using Intelligent MPPT controller

Yakhelef Yassine
Laboratory of Automation and
Informatics-Guelma, LAIG
University of Boumerdes, 35000, Algeria

Herkat Wiam
Laboratory of Signals and Systems, LSS
University of Boumerdes, 35000, Algeria

Abstract

while it provides perfectly clean electricity without any environmental effect, solar energy is the most abundant and free renewable energy source worldwide. However, because of its highly dependency on the weather condition variation particularly those of operating temperature and sunlight irradiance, the solar based electrical energy conversion system is characterized with lot of energy wastage and noticeable low efficiency, which requires an appropriate and effective design of its control part and components for enhancing its generation and delivery performance. The purpose in this work is to perform an investigate study and simulation under Matlab/Simulink environment of the behaviour and reaction of the artificial neural network (ANN) based MPPT controller under various and different climatic condition characterized particularly by the rate of the sunlight intensity variation during the day. Different weather situations regarding the sunlight intensity rate variation ranging from slow to harsh and severe changes are considered and applied in order to study the dynamic performance of the MPPT controller for improving the power quality generation as well as the dynamic performance of the grid tied solar conversion system when implemented around the modular multilevel converter as the newly power conversion emerged technology whatever these atmospheric situations. The simulation results have shown the superiority and outstanding of the ANN MPPT controller in terms of the output power quality and dynamic performance in reaching and retaining the stability at the higher power level regardless of the weather change.

Keywords

Microgrid solar system - Modular Multilevel Converter (MMC) - ANN - MPPT controller - Power quality - Dynamic performance.





2nd National Conference on Green Energy
NCGE'24
15th & 16th December 2024
Boumerdes - Algeria



Paper ID : 89

Prediction of Engine Performance for an Hydrogen Dual Fueled Diesel Engine using Artificial Neural Network

OUCHIKH Sarah
LEMI Laboratory
UMBB University, Boumeredes, Algeria

LOUNICI Mohand Said
LEMI Laboratory
UMBB University, Boumeredes, Algeria

Abstract

The present study investigates the use of Artificial Neural Network (ANN) modeling for prediction of performance characteristics of natural gas/diesel engine enriched with Hydrogen in dual fuel mode. ANN model was developed with two input parameters, load and hydrogen flow rate to predict the performance characteristics represented by the brake thermal efficiency (BTE) and the brake specific fuel consumption (BSFC). The trained ANN models were evaluated for various transfer functions by varying the number of neurons in the hidden layers. Logarithmic sigmoid and hyperbolic tangent sigmoid transfer function for Levenberg-Marquardt was found to be having best regression value. The overall regression coefficient (R^2), MSE and MAPE for the model developed are 0.99360, 0.0011 and 4.863001% respectively.

Keywords

Alternative fuels - Hydrogen - Performance - Artificial neural network.





2nd National Conference on Green Energy
NCGE'24
15th & 16th December 2024
Boumerdes - Algeria



Paper ID : 90

Optimization of Heat Exchanges in Forced Convection at the Level of a Fin Exchanger

Guemmadi Messaouda
Laboratory of Mechanical Energetics and
Engineering
Department of Mechanical Engineering,
Faculty of Technology, University of
Boumerdes, Algeria

Brahimi Faiza
Laboratory of Dynamic Motors and Vibro
acoustic
Department of Mechanical Engineering,
Faculty of Technology, University of
Boumerdes, Algeria

Abstract

The heat exchanges, in forced convection, of a condenser forming part of an air conditioner, in vertical position were numerically modeled by a program written under Matlab software. The simulation and the processing of the exchanges are carried out by optimizing the exchange coefficient as well as the power exchanged per linear meter of condenser. The results obtained allow an optimal dimensioning of the systems that can be used in different operating conditions.

Keywords





2nd National Conference on Green Energy
NCGE'24
15th & 16th December 2024
Boumerdes - Algeria



Paper ID : 91

Advanced Photovoltaic Pumping System Modelling and MPPT Control via Bond Graph

Said ALEM
Laboratory of Solid
Mechanics and Systems
LMSS, University
M'Hamed Bougara
Boumerdes, Algeria

Bilal BENCHABLA
Laboratory of Solid
Mechanics and Systems
LMSS, University
M'Hamed Bougara
Boumerdes, Algeria

Sofiane BERRAZOUANE
Laboratory of Solid
Mechanics and Systems
LMSS, University
M'Hamed Bougara
Boumerdes, Algeria

Djamel BENAZZOZ
Laboratory of Solid
Mechanics and Systems
LMSS, University
M'Hamed Bougara
Boumerdes, Algeria

Abstract

This study focuses on utilizing solar energy to generate electricity for powering a water pump via electric motors, highlighting the principle of photovoltaic pumping. Initially, we explain the photovoltaic effect and describe the various components of a photovoltaic system. We then model our solar pumping system, which includes a photovoltaic generator, a DC motor, and a DC/DC converter, using the bond graph method, a modern approach for modelling multidisciplinary systems. Following this, we examine several MPPT control methods, such as perturb and observe control, hill climbing control, and incremental conductance control. Ultimately, we propose a novel MPPT control based on bond graph principles and characteristic laws that influence the current and voltage at the output of the photovoltaic generator, allowing for control of the chopper without utilizing the duty cycle (α).

Keywords

MPPT - Photovoltaics - Pumping - Bond Graph - DC motor - DC/DC converter

